



B43540A5277M7 Information

M Ca Heisener.com

Part Number B43540A5277M7
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 270UF 20% 450V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43540A5277M7 Specifications

Manufacturer Part Number B43540A5277M7 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43540A5277M7
Package Radial, Can - Snap-In Series B43540 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43540 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43540 Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 390 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43540
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 4900 Hz 390 mOhm @ 100Hz 10000 Hrs @ 85°C -40°C ~ 85°C 6eneral Purpose 2.12A @ 100Hz 2.12A @ 100Hz 1.181" Dia (30.00mm) 1.181" Dia (30.00mm) Through Hole Radial, Can - Snap-In	Capacitance	270μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case R390 mOhm @ 100Hz 1000Hz 10000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 85°C -40°C ~ 85°C Folar General Purpose 2.12A @ 100Hz - 1.181" Dia (30.00Hz) 1.181" Dia (30.00Hz) Through Hole Radial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency	ESR (Equivalent Series Resistance)	390 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.12A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.394" (10.00mm) Size / Dimension Light - Seated (Max) Lead Size Mount Land Size Through Hole Package / Case 2.12A @ 100Hz 2.	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - Low Frequency	2.12A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.654" (42.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43540A5277M7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540A5277M7 Payment Methods



















B43540A5277M7 Shipping Methods













If you have any question about B43540A5277M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com