



B43540A9397M80 Information

Part Number B43540A9397M80
Manufacturer EPCOS (TDK)
Category Capacitors
Aluminum Electroly

Aluminum Electrolytic Capacitors

Description CAP ALUM 390UF 20% 400V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43540A9397M80 Specifications

Manufacturer Part Number B43540A9397M80 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 390μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Operating Temperature -40°C ~ 85°C Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - 1 Impedance 190 mOhms 1 Lead Spacing 0.394" (10.00mm) 1 Size / Dimension 1.181" Dia (30.00mm) 1 Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - 1 Mounting Type Through Hole Package / Case Report errors?	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 390µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43540A9397M80
Package Radial, Can - Snap-In Series B43540 Capacitance 390μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43540 Capacitance 390μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43540 Capacitance 390µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 390µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43540
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 160 mOhm @ 100Hz 100Hz -40°C ~ 85°C -40°C ~ 80°C -40°C ~ 85°C -40°C ~ 80°C -40°C ~	Capacitance	390μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~ 85°C	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.78A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.78A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.858" (47.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	190 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.858" (47.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
Transfer and the second		Report errors?

B43540A9397M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540A9397M80 Payment Methods



















B43540A9397M80 Shipping Methods













If you have any question about B43540A9397M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com