

B43540B2158M60

equest a Quote

B43540B2158M60 Information

Part Number	B43540B2158M60
Manufacturer	EPCOS (TDK)
Category Description Package	Capacitors Aluminum Electrolytic Capacitors
	CAP ALUM 1500UF 20% 200V SNAP
	Radial, Can - Snap-In
	For the pricing/inventory/lead time, please contact
	us Website: https://www.heisener.com E-mail: salesdept@heisener.com
	Manufacturer Category Description

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540B2158M60 Specifications

Manufacturer Part Number B43540B2158M60 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 1500µF Tolerance 200V Strike Resistance) 60m Ohm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 4.69A @ 100Hz Impedance 75 mOhms Lead Spacing 0.394° (10.00mn) Size / Dinension 1.654° (42.00mm) Size / Dinension 1.654° (42.00mm) Size / Dinension - Mounting Type - Mounting Type Radial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFnrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540B2158M60
IdentifyAluminut Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43540Capacitance1500µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzDifterime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency6Impedance75 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Hight - Seated (Max).Surface Mount Land Size-Hounting TypeFinogh HolePackage / CaseStail, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance1500µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)60 mOhm @ 100HzDerating Temperature10000 Hrs @ 85°COperating Temperaturee40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lead Spacing1.378" Dia (35.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance75 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1500µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzInpedance75 mOhmsIsze / Dimension1.378" Dia (35.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-<	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Pockage / CaseRatial, Can - Snap-In	Series	B43540
Voltage - Rated200VESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzImpedance75 mOhmsIcad Spacing0.394" (10.00mm)Size / Dinension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1500µF
CGESR (Equivalent Series Resistance)60 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	60 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.678" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency4.69A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	4.69A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	75 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In
1		Report errors?

B43540B2158M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.




Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540B2158M60 Payment Methods





E-mail: salesdept@heisener.com