



B43540B2567M2 Information

Heisener.com

Part Number B43540B2567M2
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 560UF 20% 200V SNAP

PackageRadial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43540B2567M2 Specifications

| Manufacturer Part Number B43540B2567M2 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | | |
|--|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 560µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer Part Number | B43540B2567M2 |
| Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 560µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Manufacturer | EPCOS (TDK) |
| Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Category | Capacitors |
| Series B43540 Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | | Aluminum Electrolytic Capacitors |
| Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Package | Radial, Can - Snap-In - 3 Lead |
| Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 150 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Series | B43540 |
| Voltage - Rated200VESR (Equivalent Series Resistance)150 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.36A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Capacitance | 560μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Riovo Anno Anno Anno Anno Anno Anno Anno A | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 10000 Hrs @ 85°C -40°C ~ 85°C -40°C ~ 85°C -40°C ~ 85°C General Purpose 2.36A @ 100Hz - 10000 Hrs @ 85°C - 40°C ~ 85°C - 8000 Hrs @ 85°C - 10000 Hrs @ 8000 Hrs @ 8000 - 10000 Hrs @ 8000 - 1 | Voltage - Rated | 200V |
| Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | ESR (Equivalent Series Resistance) | 150 mOhm @ 100Hz |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lifetime @ Temp. | 10000 Hrs @ 85°C |
| Applications General Purpose Ripple Current - Low Frequency 2.36A @ 100Hz Ripple Current - High Frequency - Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Operating Temperature | -40°C ~ 85°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Polarization | Polar |
| Ripple Current - High Frequency Impedance Impedance Iead Spacing O.394" (10.00mm) Size / Dimension I.181" Dia (30.00mm) Height - Seated (Max) I.260" (32.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Applications | General Purpose |
| Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - Low Frequency | 2.36A @ 100Hz |
| Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Ripple Current - High Frequency | - |
| Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Impedance | 190 mOhms |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Size / Dimension | 1.181" Dia (30.00mm) |
| Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Height - Seated (Max) | 1.260" (32.00mm) |
| Package / Case Radial, Can - Snap-In - 3 Lead | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Paport arrors? | Package / Case | Radial, Can - Snap-In - 3 Lead |
| Report chors: | | Report errors? |

B43540B2567M2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540B2567M2 Payment Methods



















B43540B2567M2 Shipping Methods













If you have any question about B43540B2567M2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com