



#### B43540B2827M2 Information

Heisener.com

Part Number B43540B2827M2 Manufacturer EPCOS (TDK)

Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 820UF 20% 200V SNAP

Radial, Can - Snap-In - 3 Lead **Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43540B2827M2 Specifications**

Manufacturer Part Number         B43540B2827M2           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         820μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         100 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -	•	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         820µF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         100 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -	Manufacturer Part Number	B43540B2827M2
Aluminum Electrolytic Capacitors  Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 820µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 130 mOhms Lead Spacing 130 mOhms Lead Spacing 3ize / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size  Adaptications Radial, Can - Snap-In - 3 Lead Radial, Can - Snap-In - 3 Lead Sacing 8143540 820µF	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance\$20µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.97A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-	Category	Capacitors
Series         B43540           Capacitance         820μF           Tolerance         ±20%           Voltage - Rated         200V           ESR (Equivalent Series Resistance)         100 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         2.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         130 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.181" Dia (30.00mm)           Height - Seated (Max)         1.457" (37.00mm)           Surface Mount Land Size         -		Aluminum Electrolytic Capacitors
Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.97A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 200V  ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 130 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -	Series	B43540
Voltage - Rated 200V  ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 130 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -	Capacitance	820μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  100 mOhm @ 100Hz  10000 Hrs @ 85°C  -40°C ~ 85°C  Polar  -40°C ~ 85°C	Tolerance	±20%
Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size -	Voltage - Rated	200V
Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  130 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  Surface Mount Land Size  -40°C ~ 85°C  Polar  -40°C ~ 85°C  Polar  -40°C ~ 85°C  Seneral Purpose  1.97 (300Hz  -40°C ~ 85°C  Polar  1.90 (200	ESR (Equivalent Series Resistance)	100 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 2.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 130 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.181" Dia (30.00mm)  Height - Seated (Max) 1.457" (37.00mm)  Surface Mount Land Size -	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose  Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Inpedance Isan mohms Lead Spacing Isan mohms Lead Spacing Isan mohms Isize / Dimension Isan mohms Isize / Dimension Isan mohms Isize / Isa	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  130 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.181" Dia (30.00mm)  Height - Seated (Max)  1.457" (37.00mm)  Surface Mount Land Size  -	Polarization	Polar
Ripple Current - High Frequency       -         Impedance       130 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.457" (37.00mm)         Surface Mount Land Size       -	Applications	General Purpose
Impedance       130 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.457" (37.00mm)         Surface Mount Land Size       -	Ripple Current - Low Frequency	2.97A @ 100Hz
Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.181" Dia (30.00mm)         Height - Seated (Max)       1.457" (37.00mm)         Surface Mount Land Size       -	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-	Impedance	130 mOhms
Height - Seated (Max)  Surface Mount Land Size  1.457" (37.00mm)  -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	1.181" Dia (30.00mm)
	Height - Seated (Max)	1.457" (37.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In - 3 Lead	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

#### B43540B2827M2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43540B2827M2 Payment Methods**



















### **B43540B2827M2 Shipping Methods**













If you have any question about B43540B2827M2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com