



B43540B2827M62 Information

Heisener.com

Part NumberB43540B2827M62ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 200V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43540B2827M62 Specifications

Manufacturer Part Number B43540B2827M62 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 820µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 100000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead		
Category Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 820µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Manufacturer Part Number	B43540B2827M62
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance\$20μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.97A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In - 3 Lead Series B43540 Capacitance 820μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Category	Capacitors
Series B43540 Capacitance 820µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole		Aluminum Electrolytic Capacitors
Capacitance 820μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 100 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Inpedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.97A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43540
Voltage - Rated200VESR (Equivalent Series Resistance)100 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.97A @ 100HzRipple Current - High Frequency-Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	820μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 1000 mOhm @ 100Hz 100 mOhm @ 100Hz 1000 mChm @ 150 mCh 40°C ~ 85°C Polar -40°C ~ 85°C General Purpose 1.30 mOhms 1.30 mOhms 1.30 mOhms 1.445° (30.00mm) 1.457" (37.00mm) Through Hole	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type 110000 Hrs @ 85°C -40°C ~ 85°C General Purpose 1.00Hz 1.00Hz 1.00Hz 1.10Hy 1.00mm 1.11Hy 1.00mm 1.11Hy 1.00mm 1.11Hy 1.00mm 1.	Voltage - Rated	200V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	100 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.97A @ 100Hz Ripple Current - High Frequency - Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type General Purpose 2.97A @ 100Hz - 130 mOhms 0.394" (10.00mm) 1.181" Dia (30.00mm) 1.457" (37.00mm) Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing O.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2.97A @ 100Hz - 130 mOhms 1.30 mOhms 1.394" (10.00mm) 1.457" (37.00mm) Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 130 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Applications	General Purpose
Impedance130 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	2.97A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.457" (37.00mm) Surface Mount Land Size - Mounting Type Through Hole	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	130 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type 1.457" (37.00mm) - Through Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.457" (37.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In - 3 Lead	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In - 3 Lead
Report errors?		Report errors?

B43540B2827M62 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540B2827M62 Payment Methods



















B43540B2827M62 Shipping Methods













If you have any question about B43540B2827M62, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com