

B43540B9187M80

B43540B9187M80 Information

Heisener.com	 B43540B9187M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 180UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540B9187M80 Specifications

Manufacturer Part NumberB43540B9187M80ManufacturerEPCOS (TDK)CategoryCapacitorsAluninum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhmer 100HzDierating Temperature0000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsRener PurposeRipple Current - High Frequency1.59A @ 100HzLied Spacing0.394" (10.00mm)Lied Spacing1.81" Dia (30.00mm)Size / Dinension1.268" (32.20mm)Munting TypeFineugenceRingel Case2.000 HrselSurface Mount Land Size1.500 HolePolace1.500 HoleSurface Mount Land Size1.500 HolePolace1.500 HolePolace1.500 HoleSurface Mount Land Size1.500 HolePolace1.500 HolePolace1.500 HoleSurface Mount Land Size1.500 HolePolace1.500 Hole <th>-</th> <th></th>	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540B9187M80
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperaturee40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance.390 mOhmsLad Spacing.394" (10.0mm)Size / Dimension.181" Dia (30.00mm)Size / Dimension.181" Dia (30.00mm)Surface Mount Land Size.Mounting TypeFolage Land Shap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature44°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.59A @ 100HzKipple Current - High Frequency.90 mOhmsLead Spacing309 mOhmsLead Spacing.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).268" (32.20mm)Surface Mount Land Size.Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzInpedance300 mOhmsSize / Dimension1.181" Dia (30.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Hounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance180µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzInpedance309 mOhmsSize / Dimension1.181" Dia (30.00mm)Size / Dimension1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzImpedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43540
Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzImpedance390 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFnough Lande SeatedPackage / CaseRatial, Can - Snap-In	Capacitance	180µF
C330 mOhm @ 100HzESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFurquencyPackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	330 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.59A @ 100HzRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance390 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.59A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	390 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report en		Report errors?

B43540B9187M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540B9187M80 Payment Methods



If you have any question about B43540B9187M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com