

B43540C2827M67

B43540C2827M67 Information

Heisener.com	 B43540C2827M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540C2827M67 Specifications

CategoryCapacitorsCadegoryAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance140 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540C2827M67
Aluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43540Capacitance820µFTolerance20%Voltage - Rated00VESR (Equivalent Series Resistance)110 mOhm @ 100HzDieraing Temperature10000 Hrs @ S5°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency3.22A @ 100HzRipple Current - High Frequency3.94" (10.00mm)Lad Spacing0.394" (10.00mm)Siz / Dimension1.60" (32.00mm)Hight - Seated (Max)3.60" (32.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance\$20µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications3.22A @ 100HzRipple Current - Low Frequency.3.22A @ 100HzRipple Current - High Frequency.1000 mohmsLied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications3.22A @ 100HzRipple Current - High Frequency.Impedance140 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance820μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzInpedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.250" (32.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzImpedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43540
Voltage - Rated200VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzImpedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can - Snap-In	Capacitance	820µF
LI 10 mOhm @ 100HzESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	110 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.22A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.22A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	140 mOhms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43540C2827M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540C2827M67 Payment Methods





If you have any question about B43540C2827M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com