



#### B43540C5187M2 Information

Heisener.com

Part Number B43540C5187M2
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 180UF 20% 450V SNAP

PackageRadial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **B43540C5187M2 Specifications**

Manufacturer Part Number         B43540C5187M2           Manufacturer         EPCOS (TDK)           Category         Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         540 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.69A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	_	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         540 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.69A @ 100Hz           Ripple Current - High Frequency         -           Impedance         770 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43540C5187M2
Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         180µF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         540 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.69A @ 100Hz           Ripple Current - High Frequency         -           Impedance         770 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
Package       Radial, Can - Snap-In - 3 Lead         Series       B43540         Capacitance       180μF         Tolerance       ±20%         Voltage - Rated       450V         ESR (Equivalent Series Resistance)       540 mOhm @ 100Hz         Lifetime @ Temp.       10000 Hrs @ 85°C         Operating Temperature       -40°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       1.69A @ 100Hz         Ripple Current - High Frequency       -         Impedance       770 mOhms         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.378" Dia (35.00mm)         Height - Seated (Max)       1.260" (32.00mm)         Surface Mount Land Size       -         Mounting Type       Through Hole         Package / Case       Radial, Can - Snap-In - 3 Lead	Category	Capacitors
Series         B43540           Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         540 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.69A @ 100Hz           Ripple Current - High Frequency         -           Impedance         770 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance         180μF           Tolerance         ±20%           Voltage - Rated         450V           ESR (Equivalent Series Resistance)         540 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.69A @ 100Hz           Ripple Current - High Frequency         -           Impedance         770 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) 540 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.69A @ 100Hz  Ripple Current - High Frequency -  Impedance 770 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43540
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  - Impedance  770 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  400 C ~ 85°C  General Purpose  General Purpose  1.69A @ 100Hz  1.69A @ 100Hz  1.69A @ 100Hz  1.70 mOhms  1.378" Dia (35.00mm)  1.378" Dia (35.00mm)  Through Hole  Radial, Can - Snap-In - 3 Lead	Capacitance	180μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.69A @ 100Hz  Ripple Current - High Frequency  Impedance  770 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.69A @ 100Hz  Ripple Current - High Frequency  - Impedance  770 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.69A @ 100Hz Ripple Current - High Frequency - Impedance 770 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	540 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.69A @ 100Hz  Ripple Current - High Frequency -  Impedance 770 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 1.69A @ 100Hz Ripple Current - High Frequency	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance T70 mOhms Lead Spacing Current - Dimension Lead Spacing Current - High Frequency T70 mOhms Lead Spacing T1.378" Dia (35.00mm) Lead Spacing T1.378" Dia (35.00mm) Lead Spacing T1.260" (32.00mm)	Polarization	Polar
Ripple Current - High Frequency Impedance 770 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.69A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	770 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

#### B43540C5187M2 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43540C5187M2 Payment Methods**



















### **B43540C5187M2** Shipping Methods













If you have any question about B43540C5187M2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com