

B43540C5187M82

B43540C5187M82 Information

Manua Catego Descri	 B43540C5187M82 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 180UF 20% 450V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540C5187M82 Specifications

CategoryCapacitorsCapacitorsRadial, Can - Snap-In - 3 LeadPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance180μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43540C5187M82
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance180µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.0mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance180µFTolerance-20%Voltage - Rated450VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications1.69A @ 100HzRipple Current - Low Frequency-Impedance770 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFhoregatencePackage / CaseKadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series B43540 Capacitance 180μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 540 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar General Purpose Applications General Purpose Ripple Current - Low Frequency -69A @ 100Hz Lied Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)540 mohm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzImpedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In - 3 Lead	Series	B43540
Voltage - Rated450VESR (Equivalent Series Resistance)540 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzImpedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFurous HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	180µF
ESR 540 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 1.69A @ 100Hz Impedance - Impedance 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.69A @ 100Hz Ripple Current - High Frequency - Impedance 770 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.268" (32.20mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Katial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	540 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.69A @ 100HzRipple Current - High Frequency-Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance770 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.69A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	770 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43540C5187M82 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540C5187M82 Payment Methods



If you have any question about B43540C5187M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com