



### B43540C9227M002 Information

Heisener.com

Part Number B43540C9227M002
Manufacturer EPCOS (TDK)

**Category** Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 220UF 20% 400V SNAP

Package Radial, Can - Snap-In - 3 Lead

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43540C9227M002 Specifications**

Manufacturer Part Number         B43540C9227M002           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         220µF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         280 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         1.97A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         280 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         330 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43540C9227M002
Package         Radial, Can - Snap-In - 3 Lead           Series         B43540           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         280 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         330 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance220μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
Series         B43540           Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         280 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         330 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance         220μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         280 mOhm @ 100Hz           Lifetime @ Temp.         10000 Hrs @ 85°C           Operating Temperature         -40°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         1.97A @ 100Hz           Ripple Current - High Frequency         -           Impedance         330 mOhms           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)           Surface Mount Land Size         -           Mounting Type         Through Hole           Package / Case         Radial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 280 mOhm @ 100Hz  Lifetime @ Temp. 10000 Hrs @ 85°C  Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 330 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Heigh - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43540
Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Capacitance	220μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  10000 Hrs @ 85°C  Operating Temperature  -40°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  1.97A @ 100Hz  Ripple Current - High Frequency  Impedance  330 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -40°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  1.97A @ 100Hz  Ripple Current - High Frequency  Impedance  330 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature -40°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 330 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	280 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 1.97A @ 100Hz  Ripple Current - High Frequency -  Impedance 330 mOhms  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  1.97A @ 100Hz  Ripple Current - High Frequency  - Impedance  330 mOhms  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)  Surface Mount Land Size  - Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Impedance Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case  1.97A @ 100Hz 1.97A @ 100Hz 1.97A @ 100Hz 1.378 Dia (35.00mm)  1.378" Dia (35.00mm) 1.260" (32.00mm) 1.260" (32.00mm)  Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance 330 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.97A @ 100Hz
Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)  Surface Mount Land Size -  Mounting Type Through Hole  Package / Case Radial, Can - Snap-In - 3 Lead	Impedance	330 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Through Hole  Package / Case  Radial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -  Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

### **B43540C9227M002 Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43540C9227M002 Payment Methods



















## B43540C9227M002 Shipping Methods













If you have any question about B43540C9227M002, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com