

B43540C9227M87

B43540C9227M87 Information

	Code lenser .com	B43540C9227M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 220UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540C9227M87 Specifications

Manufacturer Part NumberB43540C9227M87Manufacturer AEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance220µFTolerance220µFVoltage - Rated400VESK (Equivalent Series Resistance)280 mOhm @ 100HzDerating Temperature9000 Hrs @ 85°COperating Temperature9000 Hrs @ 85°CPolarizationPolareaApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzLied Spacing330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Auring Type1.700 HolePackage / CaseScan Sear-In	_	
CategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLized Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540C9227M87
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance220µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature440°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance20μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzKipple Current - High Frequency-Impedance0.394" (10.0mm)Lied Spacing1.378" bia (35.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzInpedance330 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.268° (32.20mm)Height - Seated (Max)-Mounting TypeThrough HolePoackage / CaseKalial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance220µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzImpedance330 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max).Surface Mount Land Size-Pockage / CaseRidal, Can - Snap-In	Series	B43540
Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzImpedance330 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeForage Allon All	Capacitance	220µF
ESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	280 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.97A @ 100HzRipple Current - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
Heigher Gurrent - High Frequency-Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.97A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	330 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report errors		Report errors?

B43540C9227M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540C9227M87 Payment Methods





If you have any question about B43540C9227M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com