

B43540E2108M2

Request a Quote

B43540E2108M2 Information

Heisener.com	Part Number	B43540E2108M2
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 1000UF 20% 250V SNAP
	Package	Radial, Can - Snap-In - 3 Lead
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540E2108M2 Specifications

Manufacturer Part NumberB43540E2108M2ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKaiqial, Can - Snap-In - 3 Lead	•	
CategoryCapacitorsAuminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency396A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Sirder Mount Land Size-Mounting TypeFhrough HolePackage / CaseKadia, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43540E2108M2
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplications396A @ 100HzRipple Current - Low Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzInpedance85 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzImpedance85 mOhmsSize / Dimension1.81" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseStail, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Total±20%Yoltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzImpedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Series	B43540
Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzImpedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeForageMandePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	1000µF
Form 70 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.96A @ 100Hz Impedance S mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.850" (47.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Folaga Land State	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	70 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	3.96A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	85 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report error	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43540E2108M2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540E2108M2 Payment Methods





If you have any question about B43540E2108M2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com