

B43540E2108M67

B43540E2108M67 Information

Heisener.com	 B43540E2108M67 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540E2108M67 Specifications

Manufacturer Part Number B43540E2108M67 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 1000µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 700 mDm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 396A @ 100Hz Impedance 85 mOhns Lead Spacing 0.394" (10.00mm) Size / Dimension 1.81" bia (30.00mm) Size / Dimension 550" (47.00mm) Height - Seated (Max) 550" (47.00mm) Gurup Hole 1.80" (Montuntal Size Mounting Type - Mounting Type -	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540E2108M67
IdentifyAluminur Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications3.96A @ 100HzRipple Current - High Frequency3.96A @ 100HzImpedance5.90MmsLad Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mM)Hight - Seated (Max).850" (47.00mm)Surface Mount Land Size.Hounting TypeFrequencyRackage / CaseMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzImpedance0.394" (10.00mm)Lied Spacing1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Pounting TypeForoghanelPackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency396A @ 100HzLiead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetim @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency396A @ 100HzInpedance85 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.81" Dia (30.00mm)Size / Dimension1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKaila, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzImpedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can - Snap-In	Series	B43540
Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency396A @ 100HzImpedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1000µF
FSR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).Surface Mount Land Size-Mouning Type-Package / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	70 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ripple Current - Low Frequency3.96A @ 100HzRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance85 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.96A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	85 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43540E2108M67 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540E2108M67 Payment Methods



If you have any question about B43540E2108M67, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com