

B43540E2188M87

Request a Quote

B43540E2188M87 Information

Heisener.com	Part Number	B43540E2188M87	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 1800UF 20% 250V SNAP	
	Package	Radial, Can - Snap-In	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540E2188M87 Specifications

Manufacturer Part Number B43540E2188M87 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43540 Capacitance 1800µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 40 mOhm @ 100Hz Lifetime @ Temp. 000H rrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Folar Applications General Purpose Ripple Current - High Frequency 5.89A @ 100Hz Impedance 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Jize / Dimension 2.32° (57.20mm) Sirade Mount Land Size - Mounting Type Through Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance0394" (10.00mm)Lized Spacing1.378" Dia (35.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.52" (57.20mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43540E2188M87
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)0000 Hrs @ 85°COperating Temperature00000 Hrs @ 85°COperating Temperature60ereral PurposeApplications5.89A @ 100HzRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.52" (57.20mm)Surface Mount Land Size-Hounting TypeRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.522" (57.20mm)Height - Seated (Max)2.522" (57.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance1800µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzInpedance0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.252" (57.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance180μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzInpedance5.00MnmSize / Dimension1.378° Dia (35.00mm)Size / Dimension2.522° (57.20mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Totance±0%Voltage - Rated250VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzImpedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.522" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43540
Voltage - Rated250VESR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzImpedance50 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can - Snap-In	Capacitance	1800µF
FSR (Equivalent Series Resistance)40 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.522" (57.20mm)Surface Mount Land Size-Mounting TypeFackage / Case	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeFackage / Case	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	40 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency5.89A @ 100HzRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	5.89A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	50 mOhms
Height - Seated (Max)2.252" (57.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	2.252" (57.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Dt-	Package / Case	Radial, Can - Snap-In
Keport err		Report errors?

B43540E2188M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540E2188M87 Payment Methods





If you have any question about B43540E2188M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com