

B43540E2277M60

B43540E2277M60 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43540E2277M60 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540E2277M60 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzDiperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency.Lipedance320 mOhmsLipedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting TypeFincuga HalePackage / CaseMaila, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43540Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzDiperating Temperature10000 Hrs @ 85°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency.Impedance320 mOhmsLied Spacing320 mOhmsSize / Dimension0.984* Dia (25.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting Type-Package / CaseMain Land SizePackage / CaseRadia, Can - Snap-In	Manufacturer Part Number	B43540E2277M60
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43540Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.663" (27.00mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43540Capacitance270µFTolerance220%Voltage - Rated250VESR (Equivalent Series Resistance)70 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency320 mOhmsLied Spacing0.394" (10.0mm)Siz / Dimension0.984" Dia (25.00mm)Siz / Dimension1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFolared MacinePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43540Capacitance270µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.1.52A @ 100HzLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).1063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 270 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.52A @ 100Hz Impedance 320 mOhms Lead Spacing 0.994" 101.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzImpedance320 mOhmsLead Spacing0.984" Dia (25.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43540
Voltage - Rated250VESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzImpedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFuncy HolePackage / CaseRatial, Can - Snap-In	Capacitance	270µF
ESR (Equivalent Series Resistance)270 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzImpedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.063" (27.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	270 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.52A @ 100HzRipple Current - High Frequency-Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance320 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.52A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	320 mOhms
Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can - Snap-In
		Report errors?

B43540E2277M60 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540E2277M60 Payment Methods



If you have any question about B43540E2277M60, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com