

B43540E2397M82

Request a Quote

B43540E2397M82 Information

| Heisener.com | Part Number | B43540E2397M82 | |
|--------------------|--------------|---|--|
| | Manufacturer | EPCOS (TDK) | |
| | Category | Capacitors Aluminum Electrolytic Capacitors | |
| | Description | CAP ALUM 390UF 20% 250V SNAP | |
| | Package | Radial, Can - Snap-In - 3 Lead | |
| | | For the pricing/inventory/lead time, please contact | |
| For Reference Only | | us | |
| | | Website: https://www.heisener.com | |
| | | E-mail: salesdept@heisener.com | |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43540E2397M82 Specifications

| Manufacturer Part Number B43540E2397M82 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Stries B43540 Capacitance B43540 Capacitance 390µF Tolerance ±20% Voltage - Rated 250 V ESR (Equivalent Series Resistance) 190 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency -20 mOhms Ippedance 20 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Keight - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Facie Insp. | - | |
|--|------------------------------------|---|
| CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance390µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance220 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Manufacturer Part Number | B43540E2397M82 |
| Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance390µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Snap-In - 3 LeadSeriesB43540Capacitance390µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-220 mOhmsRipple Current - High Frequency-220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Category | Capacitors |
| SeriesB43540Capacitance390µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency220 mOhmsImpedance220 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | | Aluminum Electrolytic Capacitors |
| Capacitance390μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance220 mOhmsLead Spacing0.994" 10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Package | Radial, Can - Snap-In - 3 Lead |
| Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.465" (37.20mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead | Series | B43540 |
| Voltage - Rated250VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRation Sang-In - 3 Lead | Capacitance | 390µF |
| ESR (Equivalent Series Resistance) 190 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Polar Applications General Purpose Ripple Current - Low Frequency 2A @ 100Hz Impedance 220 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) - Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead | Tolerance | $\pm 20\%$ |
| Lifetime @ Temp.10000 Hrs @ 85°CDoperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead | Voltage - Rated | 250V |
| Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2A @ 100Hz Ripple Current - High Frequency - Impedance 220 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Fhrough Hole Package / Case Radial, Can - Snap-In - 3 Lead | ESR (Equivalent Series Resistance) | 190 mOhm @ 100Hz |
| PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Lifetime @ Temp. | 10000 Hrs @ 85°C |
| ApplicationsGeneral PurposeRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance20 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Operating Temperature | $-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$ |
| InInRipple Current - Low Frequency2A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Polarization | Polar |
| Ripple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Applications | General Purpose |
| Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - Low Frequency | 2A @ 100Hz |
| Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Ripple Current - High Frequency | - |
| Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Impedance | 220 mOhms |
| Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Size / Dimension | 0.984" Dia (25.00mm) |
| Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead | Height - Seated (Max) | 1.465" (37.20mm) |
| Package / Case Radial, Can - Snap-In - 3 Lead | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors | Package / Case | Radial, Can - Snap-In - 3 Lead |
| | | Report errors? |

B43540E2397M82 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43540E2397M82 Payment Methods





If you have any question about B43540E2397M82, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com