

B43564A2828M3 Information

Heisener.com

Part Number B43564A2828M3
Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 8200UF 20% 250V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43564A2828M3 Specifications

Manufacturer Part NumberB43564A2828M3ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance8200μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16.4A @ 100HzImpedance19 mOhmsLord Sensing1348" (21.70mm)
CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance8200μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16.4A @ 100HzImpedance19 mOhms
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance\$200μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16.4A @ 100HzImpedance19 mOhms
Package Radial, Can - Screw Terminals B43564 Capacitance 8200µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Radial, Can - Screw Terminals B43564 R200µF **20% **Comparized** **25°C ~ 85°C **Comparized** **Co
SeriesB43564Capacitance8200μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)24 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16.4A @ 100HzRipple Current - High Frequency-Impedance19 mOhms
Capacitance Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization Applications Ripple Current - Low Frequency Impedance 8200µF ±20% 250V 24 mOhm @ 100Hz 15000 Hrs @ 85°C -25°C ~ 85°C Polar Polar General Purpose 16.4A @ 100Hz 19 mOhms
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 24 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.4A @ 100Hz Ripple Current - High Frequency - Impedance 19 mOhms
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 19 mOhms
ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 19 mOhms
Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.4A @ 100Hz Ripple Current - High Frequency - Impedance 19 mOhms
Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 19 mOhms
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 16.4A @ 100Hz Ripple Current - High Frequency - Impedance 19 mOhms
Applications General Purpose Ripple Current - Low Frequency 16.4A @ 100Hz Ripple Current - High Frequency - Impedance 19 mOhms
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 16.4A @ 100Hz - 19 mOhms
Ripple Current - High Frequency - Impedance 19 mOhms
Impedance 19 mOhms
Load Crooking 1 249" (21.70mm)
Lead Spacing 1.248" (31.70mm)
Size / Dimension 3.028" Dia (76.90mm)
Height - Seated (Max) 4.201" (106.70mm)
Surface Mount Land Size -
Mounting Type Chassis Mount
Package / Case Radial, Can - Screw Terminals
Report errors?

B43564A2828M3 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43564A2828M3 Payment Methods



















B43564A2828M3 Shipping Methods













If you have any question about B43564A2828M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com