

# B43564A9129M7

Request a Quote

### B43564A9129M7 Information

	Heisener.com	Part Number	B43564A9129M7
		Manufacturer	EPCOS (TDK)
		Category	Capacitors Aluminum Electrolytic Capacitors
		Description	CAP ALUM 12000UF 20% 400V SCREW
		Package	Radial, Can - Screw Terminals
			For the pricing/inventory/lead time, please contact
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## B43564A9129M7 Specifications

CategoryCapacitorsPackageRadial, Can - Screw TerminalsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance12000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance12000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance12 mOhmsLead Spacing3.583" Dia (91.00mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Manufacturer Part Number	B43564A9129M7
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43564Capacitance12000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLiad Spacing3.583" Dia (91.00mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43564Capacitance12000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplications27.6A @ 100HzRipple Current - Low Frequency-Impedance12 mOhmsLad Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
NewB43564Capacitance12000μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzLiad Spacing1.248° (31.70mm)Size / Dimension3.583° Dia (91.00mm)Height - Seated (Max)8.740° (222.00mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseKadial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance12000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Ingedance12 mOhmsLiad Spacing3.583° Dia (91.00mm)Size / Dimension3.583° Dia (91.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRatial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 15 mOhm @ 100Hz   Lifetime @ Temp. 15000 Hrs @ 85°C   Operating Temperature -25°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 27.6A @ 100Hz   Impedance 12 mOhms   Lead Spacing 3.583" Dia (91.00mm)   Size / Dimension 8.740" (222.00mm)   Surface Mount Land Size -   Mounting Type Chasis Mount   Package / Case Radial, Can - Screw Terminals	Series	B43564
Voltage - Rated400VESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzImpedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	12000µF
Constraint15 mOhm @ 100HzESR (Equivalent Series Resistance)15 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzNippedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Tolerance	$\pm 20\%$
Lifetime @ Temp.15000 Hrs @ 85°CDoperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLead Spacing3.583" Dia (91.00mm)Size / Dimension8.740" (222.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Voltage - Rated	400V
Operating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	15 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency27.6A @ 100HzRipple Current - High Frequency-Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance12 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	27.6A @ 100Hz
IILead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Impedance	12 mOhms
Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Size / Dimension	3.583" Dia (91.00mm)
Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Height - Seated (Max)	8.740" (222.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### B43564A9129M7 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43564A9129M7 Payment Methods



## B43564A9129M7 Shipping Methods



If you have any question about B43564A9129M7, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com