



#### B43564A9338M3 Information

Manufacture Category Heisener.com

Part Number B43564A9338M3 Manufacturer EPCOS (TDK)

Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 3300UF 20% 400V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43564A9338M3** Specifications

Manufacturer Part Number         B43564A9338M3           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43564           Capacitance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         54 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         −25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         9.9A @ 100Hz           Ripple Current - High Frequency         -           Impedance         43 mOhms           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43564 Capacitance 3300µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 43 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43564A9338M3
Aluminum Electrolytic Capacitors  Package Radial, Can - Screw Terminals  Series B43564  Capacitance 3300µF  Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 54 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 9.9A @ 100Hz  Ripple Current - High Frequency -  Impedance 43 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43564Capacitance3300µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)54 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency9.9A @ 100HzRipple Current - High Frequency-Lead Spacing1.122" (28.50mm)Size / Dimension2.532" Dia (64.30mm)Height - Seated (Max)4.201" (106.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series         B43564           Capacitance         3300μF           Tolerance         ±20%           Voltage - Rated         400V           ESR (Equivalent Series Resistance)         54 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         9.9A @ 100Hz           Ripple Current - High Frequency         -           Lead Spacing         1.122" (28.50mm)           Size / Dimension         2.532" Dia (64.30mm)           Height - Seated (Max)         4.201" (106.70mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance       3300µF         Tolerance       ±20%         Voltage - Rated       400V         ESR (Equivalent Series Resistance)       54 mOhm @ 100Hz         Lifetime @ Temp.       15000 Hrs @ 85°C         Operating Temperature       -25°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       9.9A @ 100Hz         Ripple Current - High Frequency       -         Impedance       43 mOhms         Lead Spacing       1.122" (28.50mm)         Size / Dimension       2.532" Dia (64.30mm)         Height - Seated (Max)       4.201" (106.70mm)         Surface Mount Land Size       -         Mounting Type       Chassis Mount         Package / Case       Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 400V  ESR (Equivalent Series Resistance) 54 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 9.9A @ 100Hz  Ripple Current - High Frequency -  Impedance 43 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	B43564
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  - Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Capacitance	3300µF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  4.201" (106.70mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  9.9A @ 100Hz  Ripple Current - High Frequency  - Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  2.532" Dia (64.30mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Voltage - Rated	400V
Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  4.201" (106.70mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	54 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 9.9A @ 100Hz  Ripple Current - High Frequency - Impedance 43 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  9.9A @ 100Hz  Ripple Current - High Frequency  - Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  2.532" Dia (64.30mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  43 mOhms  Lead Spacing  1.122" (28.50mm)  Size / Dimension  2.532" Dia (64.30mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 43 mOhms Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance 43 mOhms  Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	9.9A @ 100Hz
Lead Spacing 1.122" (28.50mm)  Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.532" Dia (64.30mm)  Height - Seated (Max) 4.201" (106.70mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	43 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size -  Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.532" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

### B43564A9338M3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43564A9338M3 Payment Methods



















## **B43564A9338M3** Shipping Methods













If you have any question about B43564A9338M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com