



B43564B2159M7 Information

Part Number B43564B2159M7 Manufacturer EPCOS (TDK) Category Capacitors Heisener.com

Aluminum Electrolytic Capacitors

Description CAP ALUM 15000UF 20% 250V SCREW

Radial, Can - Screw Terminals **Package**

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43564B2159M7 Specifications

Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43564 Capacitance 15000µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43564 Capacitance 15000µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43564B2159M7
Package Radial, Can - Screw Terminals Series B43564 Capacitance 15000μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43564 Capacitance 15000μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43564 Capacitance 15000μF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 15000µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43564
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Radial, Can - Screw Terminals	Capacitance	15000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Riono Hrs @ 85°C 15000 Hrs @ 85°C Polar 10 mOhms	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 15000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -2104	Voltage - Rated	250V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	12 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5urface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency 27.4A @ 100Hz Ripple Current - High Frequency - Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance In mohms Lead Spacing Interval 1.248" (31.70mm) Size / Dimension Interval 2.248" (31.70mm) Size / Dimension Interval 3.028" Dia (76.90mm) Surface Mount Land Size Interval 4.248" (31.70mm) Interval	Applications	General Purpose
Impedance 10 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	27.4A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 6.681" (169.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	10 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	6.681" (169.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43564B2159M7 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43564B2159M7 Payment Methods



















B43564B2159M7 Shipping Methods













If you have any question about B43564B2159M7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com