



### B43564B4109M3 Information

Heisener.com

Part Number B43564B4109M3
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

**Description** CAP ALUM 10000UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43564B4109M3 Specifications**

Manufacturer Part Number         B43564B4109M3           Manufacturer         EPCOS (TDK)           Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43564           Capacitance         10000µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         20 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         General Purpose           Ripple Current - Low Frequency         21.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         16 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.583" Dia (91.00mm)           Height - Seated (Max)         5.728" (145.50mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	_	
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - Screw Terminals           Series         B43564           Capacitance         10000µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         20 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         21.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         16 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.583" Dia (91.00mm)           Height - Seated (Max)         5.728" (145.50mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer Part Number	B43564B4109M3
Package         Radial, Can - Screw Terminals           Series         B43564           Capacitance         10000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         20 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         21.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         16 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.583" Dia (91.00mm)           Height - Seated (Max)         5.728" (145.50mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package         Radial, Can - Screw Terminals           Series         B43564           Capacitance         10000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         20 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         21.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         16 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.583" Dia (91.00mm)           Height - Seated (Max)         5.728" (145.50mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals	Category	Capacitors
Series         B43564           Capacitance         10000μF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         20 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         21.5A @ 100Hz           Ripple Current - High Frequency         -           Impedance         16 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.583" Dia (91.00mm)           Height - Seated (Max)         5.728" (145.50mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount           Package / Case         Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance       10000µF         Tolerance       ±20%         Voltage - Rated       350V         ESR (Equivalent Series Resistance)       20 mOhm @ 100Hz         Lifetime @ Temp.       15000 Hrs @ 85°C         Operating Temperature       -25°C ~ 85°C         Polarization       Polar         Applications       General Purpose         Ripple Current - Low Frequency       21.5A @ 100Hz         Ripple Current - High Frequency       -         Impedance       16 mOhms         Lead Spacing       1.248" (31.70mm)         Size / Dimension       3.583" Dia (91.00mm)         Height - Seated (Max)       5.728" (145.50mm)         Surface Mount Land Size       -         Mounting Type       Chassis Mount         Package / Case       Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 20 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 21.5A @ 100Hz  Ripple Current - High Frequency -  Impedance 16 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.583" Dia (91.00mm)  Height - Seated (Max) 5.728" (145.50mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Series	B43564
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  16 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Riound Hooms  10 mOhms  1	Capacitance	10000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  21.5A @ 100Hz  Ripple Current - High Frequency  Impedance  16 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  3.583" Dia (91.00mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp.  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  16 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  15000 Hrs @ 85°C  -25°C ~ 85°C  Reform  Foliar  Foli	Voltage - Rated	350V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 21.5A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 5.728" (145.50mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	20 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 21.5A @ 100Hz  Ripple Current - High Frequency -  Impedance 16 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.583" Dia (91.00mm)  Height - Seated (Max) 5.728" (145.50mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 21.5A @ 100Hz  Ripple Current - High Frequency Impedance I6 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.583" Dia (91.00mm) Height - Seated (Max) 5.728" (145.50mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  16 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  3.583" Dia (91.00mm)  Height - Seated (Max)  5.728" (145.50mm)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance Inpedance Iead Spacing Inserting I	Applications	General Purpose
Impedance16 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.583" Dia (91.00mm)Height - Seated (Max)5.728" (145.50mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	21.5A @ 100Hz
Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.583" Dia (91.00mm)  Height - Seated (Max) 5.728" (145.50mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.583" Dia (91.00mm)  Height - Seated (Max) 5.728" (145.50mm)  Surface Mount Land Size -  Mounting Type Chassis Mount  Package / Case Radial, Can - Screw Terminals	Impedance	16 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount  Package / Case  Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.583" Dia (91.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	5.728" (145.50mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

#### B43564B4109M3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### B43564B4109M3 Payment Methods



















## **B43564B4109M3 Shipping Methods**













If you have any question about B43564B4109M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com