



B43584A0477M000 Information

Heisener.com

Part Number B43584A0477M000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 400V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43584A0477M000 Specifications

| Manufacturer Part Number B43584A0477M000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 470µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Scries Resistance) - Lifetime @ Temp. - Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | | |
|--|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 470µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) Lifetime @ Temp | Manufacturer Part Number | B43584A0477M000 |
| PackageRadial, Can - Screw TerminalsSeriesB43584Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Manufacturer | EPCOS (TDK) |
| PackageRadial, Can - Screw TerminalsSeriesB43584Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Category | Capacitors |
| Series B43584 Capacitance 470μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. - Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | | Aluminum Electrolytic Capacitors |
| Capacitance 470μF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) - Lifetime @ Temp. - Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Package | Radial, Can - Screw Terminals |
| Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Series | B43584 |
| Voltage - Rated400VESR (Equivalent Series Resistance)-Lifetime @ TempOperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Capacitance | 470μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Polar | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case -25°C ~ 85°C Rount General Purpose -3000 | Voltage - Rated | 400V |
| Operating Temperature Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Polar Polar Current - High Frequency Polar | ESR (Equivalent Series Resistance) | - |
| Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Lifetime @ Temp. | - |
| Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Operating Temperature | -25°C ~ 85°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Radial, Can - Screw Terminals | Polarization | Polar |
| Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Applications | General Purpose |
| Impedance-Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Ripple Current - Low Frequency | - |
| Lead Spacing-Size / Dimension-Height - Seated (Max)-Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals | Ripple Current - High Frequency | - |
| Size / Dimension - Height - Seated (Max) - Surface Mount Land Size - Chassis Mount Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Impedance | - |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Lead Spacing | - |
| Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Size / Dimension | - |
| Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals | Height - Seated (Max) | - |
| Package / Case Radial, Can - Screw Terminals | Surface Mount Land Size | - |
| | Mounting Type | Chassis Mount |
| | Package / Case | Radial, Can - Screw Terminals |
| Report errors? | | Report errors? |

B43584A0477M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43584A0477M000 Payment Methods





















B43584A0477M000 Shipping Methods













If you have any question about B43584A0477M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com