



### B43584A4688M3 Information

Heisener.com

Part NumberB43584A4688M3ManufacturerEPCOS (TDK)CategoryCapacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 6800UF 20% 350V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43584A4688M3** Specifications

Manufacturer Part NumberB43584A4688M3ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesB43584Capacitance6800µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)19 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance23 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals		
Category Category Radial, Can - Screw Terminals Series Radial, Can - Screw Terminals Series B43584 Capacitance 6800µF Tolerance ±20% Voltage - Rated ESR (Equivalent Series Resistance) 19 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 23 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount	Manufacturer Part Number	B43584A4688M3
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43584Capacitance6800µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)19 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance23 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43584Capacitance6800μFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)19 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance23 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Category	Capacitors
Series         B43584           Capacitance         6800µF           Tolerance         ±20%           Voltage - Rated         350V           ESR (Equivalent Series Resistance)         19 mOhm @ 100Hz           Lifetime @ Temp.         15000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         16A @ 100Hz           Ripple Current - High Frequency         -           Impedance         23 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.028" Dia (76.90mm)           Height - Seated (Max)         5.677" (144.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount		Aluminum Electrolytic Capacitors
Capacitance6800µFTolerance±20%Voltage - Rated350VESR (Equivalent Series Resistance)19 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance23 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Package	Radial, Can - Screw Terminals
Tolerance ±20%  Voltage - Rated 350V  ESR (Equivalent Series Resistance) 19 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 16A @ 100Hz  Ripple Current - High Frequency -  Impedance 23 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 5.677" (144.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount	Series	B43584
Voltage - Rated350VESR (Equivalent Series Resistance)19 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency16A @ 100HzRipple Current - High Frequency-Impedance23 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Capacitance	6800μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  16A @ 100Hz  Ripple Current - High Frequency  Impedance  23 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  19 mOhm @ 100Hz  15000 Hrs @ 85°C  - Cassis Mount	Tolerance	±20%
Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  16A @ 100Hz  Ripple Current - High Frequency  - Impedance  23 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  3.028" Dia (76.90mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount	Voltage - Rated	350V
Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  23 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  3.028" Dia (76.90mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  -25°C ~ 85°C  General Purpose  16A @ 100Hz  1.248" (31.70mm)  5.677" (144.20mm)  Chassis Mount	ESR (Equivalent Series Resistance)	19 mOhm @ 100Hz
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 16A @ 100Hz  Ripple Current - High Frequency -  Impedance 23 mOhms  Lead Spacing 1.248" (31.70mm)  Size / Dimension 3.028" Dia (76.90mm)  Height - Seated (Max) 5.677" (144.20mm)  Surface Mount Land Size -  Mounting Type Chassis Mount	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  23 mOhms  Lead Spacing  1.248" (31.70mm)  Size / Dimension  3.028" Dia (76.90mm)  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Chassis Mount	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 23 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Polarization	Polar
Ripple Current - High Frequency Impedance 23 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Applications	General Purpose
Impedance         23 mOhms           Lead Spacing         1.248" (31.70mm)           Size / Dimension         3.028" Dia (76.90mm)           Height - Seated (Max)         5.677" (144.20mm)           Surface Mount Land Size         -           Mounting Type         Chassis Mount	Ripple Current - Low Frequency	16A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.028" Dia (76.90mm) Height - Seated (Max) 5.677" (144.20mm) Surface Mount Land Size - Mounting Type Chassis Mount	Ripple Current - High Frequency	-
Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.677" (144.20mm)Surface Mount Land Size-Mounting TypeChassis Mount	Impedance	23 mOhms
Height - Seated (Max)  Surface Mount Land Size  Mounting Type  5.677" (144.20mm)  - Chassis Mount	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount	Size / Dimension	3.028" Dia (76.90mm)
Mounting Type Chassis Mount	Height - Seated (Max)	5.677" (144.20mm)
C 31	Surface Mount Land Size	-
Package / Case Radial, Can - Screw Terminals	Mounting Type	Chassis Mount
	Package / Case	Radial, Can - Screw Terminals
Report errors?		Report errors?

### B43584A4688M3 Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43584A4688M3 Payment Methods**



















# **B43584A4688M3** Shipping Methods













If you have any question about B43584A4688M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com