



B43584A5158M000 Information

Heisener.com

Part Number B43584A5158M000
Manufacturer EPCOS (TDK)
Category Capacitors

tegory Capacitors
Aluminum Electrolytic Capacitors

Description CAP ALUM 1500UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43584A5158M000 Specifications

Manufacturer Part Number B43584A5158M000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 1500µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 1500µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43584A5158M000
Package Radial, Can - Screw Terminals Series B43584 Capacitance 1500μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
Package Radial, Can - Screw Terminals Series B43584 Capacitance 1500µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Category	Capacitors
Series B43584 Capacitance 1500µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 1500μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 99 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Rated (Max) Radial, Can - Screw Terminals	Series	B43584
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing 1.122" (28.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Pomohm @ 100Hz 15000 Hrs @ 85°C Pomohm @ 100Hz -25°C ~ 85°C Reneral Purpose General Purpose 1.122" (28.50mm) 2.532" Dia (64.30mm) 4.201" (106.70mm) Chassis Mount Radial, Can - Screw Terminals	Capacitance	1500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency Impedance Lead Spacing 1.122" (28.50mm) Size / Dimension 4.201" (106.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Polar 15000 Hrs @ 85°C Polar 25°C ~ 85°C Polar 1600 Hrs @ 85°C Polar 15000 Hrs @ 85°C Polar 1600 Hrs @ 85°C 1600 Hrs @ 85°C 1600 Hrs @ 85°C Polar 1600 Hrs @ 85°C 1600 Hrs @	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 15000 Hrs @ 85°C -25°C ~ 85°C Polar -25°C ~ 85°C -25°C ~ 85°C	Voltage - Rated	450V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 1.122" (28.50mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	99 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case General Purpose 7A @ 100Hz 1.10Hz	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency 7A @ 100Hz Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency - Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance - Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - Low Frequency	7A @ 100Hz
Lead Spacing 1.122" (28.50mm) Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.532" Dia (64.30mm) Height - Seated (Max) 4.201" (106.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.122" (28.50mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.532" Dia (64.30mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	4.201" (106.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43584A5158M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43584A5158M000 Payment Methods





















B43584A5158M000 Shipping Methods













If you have any question about B43584A5158M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com