



#### B43584A5828M3 Information

Manufactu Category

**Part Number** B43584A5828M3 **Manufacturer** EPCOS (TDK)

Category Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 8200UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **B43584A5828M3** Specifications

Manufacturer Part Number  Manufacturer  EPCOS (TDK)  Category  Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  Series  B43584  Capacitance  B43584  Capacitance  8200µF  Tolerance  ±20%  Voltage - Rated  450V  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  Low Frequency  Indeed and Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  B43584  Aluminum Electrolytic Capacitors  Aluminum Electrolytic Capacitors  B43584  Aluminum Electrolytic Capacitors  Aluminum Electrolytic Capacitors  Radial, Can - Screw Terminals  B43584  Aluminum Electrolytic Capacitors  Alum
CategoryCapacitorsPackageRadial, Can - Screw TerminalsSeriesB43584Capacitance8200μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8A @ 100HzImpedance16 mOhms
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43584Capacitance\$200μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8A @ 100HzImpedance16 mOhms
PackageRadial, Can - Screw TerminalsSeriesB43584Capacitance8200μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8A @ 100HzRipple Current - High Frequency-Impedance16 mOhms
SeriesB43584Capacitance8200μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8A @ 100HzRipple Current - High Frequency-Impedance16 mOhms
Capacitance8200μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)13 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency23.8A @ 100HzRipple Current - High Frequency-Impedance16 mOhms
Tolerance ±20%  Voltage - Rated 450V  ESR (Equivalent Series Resistance) 13 mOhm @ 100Hz  Lifetime @ Temp. 15000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 23.8A @ 100Hz  Ripple Current - High Frequency -  Impedance 16 mOhms
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  450V  450V  6450V  64
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  15000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  13 mOhm @ 100Hz  15000 Hrs @ 85°C  -25°C ~ 85°C  Polar  Polar  -25°C ~ 85°C  Polar  -25°C ~ 85°C  -25°C ~ 85
Lifetime @ Temp.  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  15000 Hrs @ 85°C  Polarization  Polar  -25°C ~ 85°C  Polarization  -23.8A @ 100Hz  -16 mOhms
Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  Impedance  -25°C ~ 85°C  Polar  Polar  -25°C ~ 85°C  Polar  Polar  -25°C ~ 85°C  -25°C ~ 85°C
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 23.8A @ 100Hz  Ripple Current - High Frequency -  Impedance 16 mOhms
Applications General Purpose Ripple Current - Low Frequency 23.8A @ 100Hz Ripple Current - High Frequency - Impedance 16 mOhms
Ripple Current - Low Frequency 23.8A @ 100Hz  Ripple Current - High Frequency -  Impedance 16 mOhms
Ripple Current - High Frequency - Impedance 16 mOhms
Impedance 16 mOhms
1 2401 (21 70 )
Lead Spacing 1.248" (31.70mm)
Size / Dimension 3.028" Dia (76.90mm)
Height - Seated (Max) 8.728" (221.70mm)
Surface Mount Land Size -
Mounting Type Chassis Mount
Package / Case Radial, Can - Screw Terminals
Report errors?

### B43584A5828M3 Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **B43584A5828M3 Payment Methods**



















## **B43584A5828M3** Shipping Methods













If you have any question about B43584A5828M3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com