



B43584B6827M000 Information

Heisener.com

For Reference Only

Part Number B43584B6827M000
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 500V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43584B6827M000 Specifications

Manufacturer Part Number B43584B6827M000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 820μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature −25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Series B43584 Capacitance 820µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension Leight - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43584B6827M000
Package Radial, Can - Screw Terminals Series B43584 Capacitance 820μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43584Capacitance820µFTolerance±20%Voltage - Rated500VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.6A @ 100HzRipple Current - High Frequency-Impedance144 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series B43584 Capacitance 820µF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 820μF Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 500V ESR (Equivalent Series Resistance) 120 mOhm @ 100Hz Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Raistance) 120 mOhm @ 100Hz 12000 Hrs @ 85°C 6eneral Purpose 4.6A @ 100Hz 1.6A @ 100Hz 1.	Series	B43584
Voltage - Rated500VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.12000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.6A @ 100HzRipple Current - High Frequency-Impedance144 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	820μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 4.63 @ 100Hz 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. 12000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	500V
Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case -25°C ~ 85°C 85°C 86°C	ESR (Equivalent Series Resistance)	120 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	12000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency 4.6A @ 100Hz Ripple Current - High Frequency - Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 144 mOhms Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance144 mOhmsLead Spacing0.874" (22.20mm)Size / Dimension2.032" Dia (51.60mm)Height - Seated (Max)3.217" (81.70mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	4.6A @ 100Hz
Lead Spacing 0.874" (22.20mm) Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 2.032" Dia (51.60mm) Height - Seated (Max) 3.217" (81.70mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	144 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	0.874" (22.20mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	2.032" Dia (51.60mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	3.217" (81.70mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43584B6827M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43584B6827M000 Payment Methods



















B43584B6827M000 Shipping Methods













If you have any question about B43584B6827M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com