

B43601A2188M000

lest a Quote

B43601A2188M000 Information

Heisener.com	Part Number	B43601A2188M000	
	Manufacturer	EPCOS (TDK)	
	Category	Capacitors Aluminum Electrolytic Capacitors	
	Description	CAP ALUM 1800UF 20% 200V SNAP	
	Package	Radial, Can - Snap-In	- 1 32
		For the pricing/inventory/lead time, please contact	نو لکا
		us Will be for the form	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601A2188M000 Specifications

Manufacturer Part NumberB43601A2188M000ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance200VVoltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzOperating Temperature40°C ~ 85°COplarizationPolarApplicationsGeneral PurposeApplications600 HzRipple Current - High Frequency4.28A @ 100HzIngedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.047" (52.00mm)Surface Mount Land Size0.40" (52.00mm)Surface Mount Land Size0.40" (52.00mm)Surface Mount Land Size0.40" (52.00mm)	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601CapacitanceB43601Capacitance±20%Yoltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency4.28A @ 100HzLiead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Manufacturer Part Number	B43601A2188M000
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzDerating Temper10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzHangeance55 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)5.047" (52.00mm)Surface Mount Land Size-	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzImpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Category	Capacitors
SeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)		Aluminum Electrolytic Capacitors
Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzIngedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzImpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)	Series	B43601
Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Capacitance	1800µF
ESR (Equivalent Series Resistance)55 mOhm @ 100HzESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	ESR (Equivalent Series Resistance)	55 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Polarization	Polar
InInRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Applications	General Purpose
Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Ripple Current - Low Frequency	4.28A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.047" (52.00mm)Surface Mount Land Size-	Impedance	75 mOhms
Height - Seated (Max) 2.047" (52.00mm) Surface Mount Land Size -	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size -	Size / Dimension	1.181" Dia (30.00mm)
	Height - Seated (Max)	2.047" (52.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report er		Report errors?

B43601A2188M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601A2188M000 Payment Methods





If you have any question about B43601A2188M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com