

B43601A2188M87

B43601A2188M87 Information

Heisener.com	 B43601A2188M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1800UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601A2188M87 Specifications

Manufacturer Part NumberB43601A2188M87ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance-20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency4.28A @ 100HzLidadgacing354" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.055" (52.20mm)Muntufa Maxie-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In	-	
CategoryCapacitorsAckageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperaturee40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43601A2188M87
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)55 mOhm @100HzDerating Temperature0000 Mrs @ 85°COparization0000 Mrs @ 85°CPolarization90araApplicationsGeneral PurposeRippe Current - Low Frequency4.28A @ 100HzRippe Current - High Frequency5 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Size / Dimension2.055" (52.20mm)Hight - Seated (Max)2.055" (52.20mm)Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzInpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Mounting TypeThrough Hole	Category	Capacitors
SeriesB43601Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzImpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance1800µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzInpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Totrance±20%Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzImpedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43601
Voltage - Rated200VESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzKipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	1800µF
ConstraintSimple ConstraintESR (Equivalent Series Resistance)55 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	55 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-40° C ~ 85° C
Ripple Current - Low Frequency4.28A @ 100HzRipple Current - High Frequency-Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a rank	Applications	General Purpose
Impedance75 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	4.28A @ 100Hz
IOutputLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	75 mOhms
Height - Seated (Max)2.055" (52.20mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	1.181" Dia (30.00mm)
Mounting Type Through Hole	Height - Seated (Max)	2.055" (52.20mm)
	Surface Mount Land Size	-
Package / Case Radial, Can - Snap-In	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report en		Report errors?

B43601A2188M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601A2188M87 Payment Methods



B43601A2188M87 Shipping Methods



If you have any question about B43601A2188M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com