

# B43601A5277M87

#### B43601A5277M87 Information

( <b>)</b> *	leisener.com Gidal terke catelore	 B43601A5277M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 270UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For R	Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43601A5277M87 Specifications

Manufacturer Part NumberB43601A5277M87ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mohm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature44°C ~ 85°CPolarzFolaraceApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzLied Spacing0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension1.858" (47.20mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Youting TypeThrough HolePower Mount Barden-Mounting Type-Power Mount Barden-Power Mount Barden-	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance0.994" (10.00mm)Liad Spacing0.994" Dia (25.00mm)Size / Dimension1.858" (47.20mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601A5277M87
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance20%Voltage - Rated50VESR (Equivalent Series Resistance)400 mOhm @ 100HzDerating Temper00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Hogh Frequency-Kipple Current - High Frequency0304° (100mm)Lead Spacing0.394° (100mm)Size / Dimension1.858° (47.20mm)Hight - Seated (Max).Surface Mount Land Size-Houning TypeMountig TypePackage / CaseMaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzDerating @ Temper10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplications6neral PurposeRipple Current - High Frequency7.14A @ 100HzRippe Current - High Frequency0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.58s" (47.20mm)Hight - Seated (Max)1.58s" (47.20mm)Surface Mount Land Size-Hounting TypeFirough HolePackage / CaseKadia, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.74A @ 100HzInpedance570 mOhmsSize / Dimension0.984" Dia (25.00mm)Size / Dimension1.858" (47.20mm)Height - Seated (Max)-Mounting TypeThrough HolePolaring TypeRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance570 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting Type-Package / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Yoltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43601
Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	270µF
C400 mOhm @ 100HzESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Inneedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadia, Can - Snap-In	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 85^{\circ}\mathrm{C}$
Ripple Current - Low Frequency1.74A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.74A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	570 mOhms
Height - Seated (Max)1.858" (47.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.858" (47.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Demost area	Package / Case	Radial, Can - Snap-In
Kepont end		Report errors?

#### B43601A5277M87 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43601A5277M87 Payment Methods





If you have any question about B43601A5277M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com