

B43601A9108M62

B43601A9108M62 Information

Contraction of the second seco	 B43601A9108M62 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 400V SNAP Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601A9108M62 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Atuminum Electrolytic Capacitors Atuminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43601 Capacitance 1000µF Tolerance ±20% Voltage - Rated 400V ESR (Equivalent Series Resistance) 110 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 0.394" (10.00mm) Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" Dia (35.00mm) Size / Dimension 2.244" (57.00mm) Height - Seated (Max) 2.244" (57.00mm)		
CapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43601Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzImpedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43601A9108M62
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43601Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Ingedance1.50 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Strace Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43601Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency3.63A @ 100HzRiple Current - High Frequency-Ingedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Sirface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43601Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzLifedme@150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Pokage / CaseKadial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Series	B43601
Voltage - Rated400VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzImpedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Package / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	1000µF
Composition110 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°CLifetime @ Temp40°C ~ 85°COperating TemperaturePolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzBipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarPolarizationsGeneral PurposeApplications3.63A @ 100HzRipple Current - Low Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarPolarizationsGeneral PurposeApplications3.63A @ 100HzRipple Current - Low Frequency3.63A @ 100HzImpedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	110 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.63A @ 100HzRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
InInRipple Current - High Frequency-Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Applications	General Purpose
Impedance150 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	3.63A @ 100Hz
I0.394" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	150 mOhms
Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In - 3 Lead
•		Report errors?

B43601A9108M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601A9108M62 Payment Methods





If you have any question about B43601A9108M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com