



B43601B2477M67 Information

(A) Heisener.com

For Reference Only

Part Number B43601B2477M67
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 470UF 20% 200V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43601B2477M67 Specifications

Manufacturer Part NumberB43601B2477M67ManufacturerEPCOS (TDK)CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance470μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.75A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)Surface Mount Land Size-		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43601 Capacitance 470μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Manufacturer Part Number	B43601B2477M67
PackageRadial, Can - Snap-InSeriesB43601Capacitance470μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)200 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.75A @ 100HzRipple Current - High Frequency-Impedance280 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.063" (27.00mm)	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43601 Capacitance 470μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Category	Capacitors
Series B43601 Capacitance 470μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)		Aluminum Electrolytic Capacitors
Capacitance 470μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Series	B43601
Voltage - Rated 200V ESR (Equivalent Series Resistance) 200 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Capacitance	470μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 1.063" (27.00mm)	Tolerance	±20%
Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Voltage - Rated	200V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	ESR (Equivalent Series Resistance)	200 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.75A @ 100Hz Ripple Current - High Frequency - Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Lifetime @ Temp.	10000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Current - Dimension Lead Spacing 1.063" (27.00mm) Current - High Frequency - 1.75A @ 100Hz - 1.00Hz - 1.00	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Polarization	Polar
Ripple Current - High Frequency Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Applications	General Purpose
Impedance 280 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Ripple Current - Low Frequency	1.75A @ 100Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Ripple Current - High Frequency	-
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.063" (27.00mm)	Impedance	280 mOhms
Height - Seated (Max) 1.063" (27.00mm)	Lead Spacing	0.394" (10.00mm)
	Size / Dimension	0.984" Dia (25.00mm)
Surface Mount Land Size -	Height - Seated (Max)	1.063" (27.00mm)
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

B43601B2477M67 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B2477M67 Payment Methods



















B43601B2477M67 Shipping Methods













If you have any question about B43601B2477M67, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com