

B43601B2567M87

Request a Quote

B43601B2567M87 Information

Heisener.com	Part Number	B43601B2567M87
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 560UF 20% 200V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601B2567M87 Specifications

Manufacturer Part Number B43601B2567M87 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43601 Capacitance Sefour Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 170 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency -99A @ 100Hz Inpedance 240 mOhms Lead Spacing 0.394 " (10.00mm) Size / Dimension 0.984" Dia (2.20mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601B2567M87
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency0.99A @ 100HzRipple Current - High Frequency0.394 " (10.00mm)Lied Spacing0.394 " (10.00mm)Siz / Dimension1.68% "G2.20mm)Hight - Seated (Max).Surface Mount Land Size-Mounting TypeFurough LandPackage / CaseKadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency240 °C mohmsLied Spacing0.394" (10.00mm)Siz / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFolarentPackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance560µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.199A @ 100HzLingedance240 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size.Mounting TypeFurough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560μFTolerance±20%Voltage Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance240 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.99A @ 100HzImpedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Series	B43601
Voltage - Rated200VESR (Equivalent Series Resistance)170 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Pokage / CaseRatial, Can - Snap-In	Capacitance	560µF
ESR 170 mOhm @ 100Hz ESR (Equivalent Series Resistance) 10000 Hrs @ 85°C Lifetime @ Temp. -40°C ~ 85°C Operating Temperature Polar Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.99A @ 100Hz Impedance 240 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.268" (32.20mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	170 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadia, Can - Snap-In	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
Ripple Current - Low Frequency1.99A @ 100HzRipple Current - High Frequency-Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance240 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.99A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	240 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43601B2567M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B2567M87 Payment Methods





If you have any question about B43601B2567M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com