

B43601B2687M80

Request a Quote

B43601B2687M80 Information

Heisener.com	Part Number	B43601B2687M80	
	Manufacturer	EPCOS (TDK)	6
	Category	Capacitors Aluminum Electrolytic Capacitors	Ş
	Description	CAP ALUM 680UF 20% 200V SNAP	
	Package	Radial, Can - Snap-In	, p
		For the pricing/inventory/lead time, please contact	Ľ
For Reference Only		us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	R

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601B2687M80 Specifications

Manufacturer Part Number B43601B2687M80 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Stries B43601 Capacitance 680µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 140 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency -27A @ 100Hz Ippedance 109 mOhms Lead Spacing 0.394" (10.00mm) Size / Dinnension 0.984" Dia (25.00mm) Surface Mount Land Size - Mounting Type - Package / Case Frough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency-Impedance190 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601B2687M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance680µFTolerance20%Voltage - Rated00VESR (Equivalent Series Resistance)140 mOhm @ 100HzDierating Temperature10000 Hrs @ St°COperating Temperature90arApplicationsGeneral PurposeRipple Current - High Frequency6Ripple Current - High Frequency0924 (10.00mm)Lided Spacing0.944 (10.00mm)Siz / Dimension0.944 (10.00mm)Siz / Dimension0.948 (10.00mm)Siz / Dimension1.465" (37.20mm)Sirafee Mount Land Size-Mounting TypeFirough HolePackage / CaseRadia, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency0.394" (10.0mm)Lied Spacing0.984" Dia (25.00mm)Siz / Dimension0.984" Dia (25.00mm)Kirface Mount Land Size-Mounting Type-Package / CaseKadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance680µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications2.27A @ 100HzRipple Current - High Frequency.Impedance190 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size.Mounting TypeFurough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance680μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzImpedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43601
Voltage - Rated200VESR (Equivalent Series Resistance)140 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzImpedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.465" (37.20mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRational Cana Cana Cana Cana Cana Cana Cana C	Capacitance	680µF
ESR 140 mOhm @ 100Hz ESR (Equivalent Series Resistance) 140 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Folar Applications General Purpose Ripple Current - Low Frequency 2.27A @ 100Hz Impedance 190 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1465" (37.20mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDoperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	140 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40° C ~ 85° C
Ripple Current - Low Frequency2.27A @ 100HzRipple Current - High Frequency-Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance190 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.27A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	190 mOhms
Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.465" (37.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43601B2687M80 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B2687M80 Payment Methods





If you have any question about B43601B2687M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com