

B43601B2827M000

B43601B2827M000 Information

Heisener.com Ontal larves data har	 B43601B2827M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 820UF 20% 200V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601B2827M000 Specifications

Manufacturer Part NumberB43601B2827M000ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzDiferium @ Temp.10000 Hrs @ 85°COperating Temp.0000 Hrs @ 85°COplarizationsGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.Linde Spacing0.394" (10.00mm)Lied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).Hounting TypeTurough HoleRowuning TypeRadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance160 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max).654" (42.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRatial, Can - Snap-In	Manufacturer Part Number	B43601B2827M000
IdentifyAluminur Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance820µFTolerance±20%Voltage - Rated00VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency5.8A @ 100HzLifetime @ Interment160 mOhmsLided Spacing0.394" (10.00mm)Size / Dimension0.394" (10.00mm)Size / Dimension1.654" (42.00mm)Hight - Seated (Max).Murting TypeThough HolePackage / CaseMaidi, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance820μFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzKipple Current - High Frequency-Impedance0.94" (10.00mm)Lead Spacing0.94" Dia (25.00mm)Size / Dimension1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFhough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency2.58A @ 100HzInpedance160 mOhmsSize / Dimension0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKalial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance820µFTolerance±20%Voltage - Rated200VESR (Equivalent Series Resistance)1000 Mrs @ 80°CLifetime @ Temp.10000 Mrs @ 80°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - High Frequency-Inpedance160 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension0.944" Dia (25.00mm)Bight - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKail, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Yoltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzImpedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Pockage / CaseRidal, Can - Snap-In	Series	B43601
Voltage - Rated200VESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzImpedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	820µF
C120 mOhm @ 100HzESR (Equivalent Series Resistance)120 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	200V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	120 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.58A @ 100HzRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a rangeRipple Current - High Frequency-Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance160 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.58A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	160 mOhms
Height - Seated (Max)1.654" (42.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.654" (42.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
D	Package / Case	Radial, Can - Snap-In
Report error		Report errors?

B43601B2827M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B2827M000 Payment Methods





If you have any question about B43601B2827M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com