

B43601B5157M62

Request a Quote

B43601B5157M62 Information

Heisener.com	Part Number	B43601B5157M62
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 150UF 20% 450V SNAP
	Package	Radial, Can - Snap-In - 3 Lead
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601B5157M62 Specifications

ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43601Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-118A @ 100HzImpedance1.02 OhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadPackageB43601Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43601B5157M62
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43601Capacitance150μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Size / Dimension1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFatogatPackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43601Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance0.394" (10.00mm)Lad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43601Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzInpedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension1.260" (32.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 720 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polar Folar Applications General Purpose Ripple Current - Low Frequency 6 Impedance 1.02 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In - 3 Lead	Series	B43601
Voltage - Rated450VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzImpedance0.20 HmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeFarcage / CasePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	150µF
For a constraint of the series Resistance)720 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Inpedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 1.18A @ 100Hz Ripple Current - High Frequency - Impedance 1.02 Ohms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 1.260" (32.00mm) Surface Mount Land Size - Mounting Type Fhough Hole Package / Case Radial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	720 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.18A @ 100HzRipple Current - High Frequency-Impedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance1.02 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.18A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	1.02 Ohms
Height - Seated (Max)1.260" (32.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.260" (32.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors'	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43601B5157M62 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B5157M62 Payment Methods



If you have any question about B43601B5157M62, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com