

B43601B5277M87

equest a Quote

B43601B5277M87 Information

C Heisener.com	Part Number	B43601B5277M87
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 270UF 20% 450V SNAP
	Package	Radial, Can - Snap-In
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601B5277M87 Specifications

Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Radial, Can - Snap-In Package Radial, Can - Snap-In Series B43601 Capacitance 270µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency - Impedance 570 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.465" (37.20mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance270μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601B5277M87
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency.176A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450 VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency.176A @ 100HzRipple Current - High Frequency-Inmedance570 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Sirface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance270µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.76A @ 100HzLifedme@570 mOhmsInpedance570 mOhmsLead Spacing.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).465" (37.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 270μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 400 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Inpedance 570 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) - Surface Mount Land Size - Polary Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.176A @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Series	B43601
Voltage - Rated450VESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Capacitance	270µF
ESR (Equivalent Series Resistance)400 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzImpedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Package / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	400 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.76A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.76A @ 100HzRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In Provide ApplyAnd the ApplyRipple Current - High Frequency-Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance570 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.76A @ 100Hz
I card Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	570 mOhms
Height - Seated (Max)1.465" (37.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.465" (37.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43601B5277M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601B5277M87 Payment Methods





If you have any question about B43601B5277M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com