

# B43601B9567M000

#### B43601B9567M000 Information

	Heisener.com	Part Number Manufacturer Category Description Package	B43601B9567M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
	For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43601B9567M000 Specifications

Manufacturer Part NumberB43601B9567M000ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance20%Voltage - Rated9000 Mnm @ 100HzESR (Equivalent Series Resistance)9000 Mnm @ 100HzOperating Temperature9000 Mrs @ 85°CPolarization60aral PurposeApplicationsGeneral PurposeApplications2.44A @ 100HzRippe Current - Low Frequency2.44A @ 100HzRippe Current - High Frequency3.39" (10.00mm)Lead Spacing3.39" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-	-	
CategoryCapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency390" (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	ufacturer Part Number	B43601B9567M000
Huminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance560μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzDierating Tempe.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications244A @ 100HzRipple Current - High Frequency-Inpedance270 mOhmsLead Spacing3094" (10.00mm)Bize / Dimension1.378" Dia (35.00mm)Hight - Seated (Max)1.457" (37.00mm)	ufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature440°C ~ 85°CPolarizationGeneral PurposeApplications2.44A @ 100HzRipple Current - High Frequency2.44A @ 100HzInpedance270 mOhmsLead Spacing0.394" (10.00mm)Height - Seated (Max)1.457" (37.00mm)	gory	Capacitors
Series B43601   Capacitance 560µF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 190 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - High Frequency -   Impedance 270 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)		Aluminum Electrolytic Capacitors
Capacitance560μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.44A @ 100HzImpedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.457" (37.00mm)	age	Radial, Can - Snap-In
Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 190 mOhm @ 100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization Polar   Applications General Purpose   Ripple Current - Low Frequency 2.44A @ 100Hz   Impedance 270 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)	25	B43601
Voltage - Rated400VESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	icitance	560µF
ESR (Equivalent Series Resistance)190 mOhm @ 100HzESR (Equivalent Series Resistance)190 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	rance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.478" Dia (35.00mm)	age - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	(Equivalent Series Resistance)	190 mOhm @ 100Hz
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	ime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	ating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.44A @ 100HzRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	rization	Polar
In PropriorIn PropriorRipple Current - High Frequency-Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	lications	General Purpose
Impedance270 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.457" (37.00mm)	le Current - Low Frequency	2.44A @ 100Hz
Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 1.457" (37.00mm)	le Current - High Frequency	-
Size / Dimension 1.378" Dia (35.00mm)   Height - Seated (Max) 1.457" (37.00mm)	edance	270 mOhms
Height - Seated (Max) 1.457" (37.00mm)	Spacing	0.394" (10.00mm)
-	/ Dimension	1.378" Dia (35.00mm)
Surface Mount Land Size -	ht - Seated (Max)	1.457" (37.00mm)
	ace Mount Land Size	-
Mounting Type Through Hole	nting Type	Through Hole
Package / Case Radial, Can - Snap-In	age / Case	Radial, Can - Snap-In
Report		Report errors

#### B43601B9567M000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43601B9567M000 Payment Methods





If you have any question about B43601B9567M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com