

B43601C5187M87

B43601C5187M87 Information

Heisener.com	 B43601C5187M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 180UF 20% 450V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601C5187M87 Specifications

Manufacturer Part NumberB43601C5187M87ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm g100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationsGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.33A @ 100HzLided Spacing0.394" (10.00mm)Lied Spacing1.181" Dia (30.00mm)Size / Dimension1.01" (27.20mm)Aufuer Add Maxima Electrolytic Capacitance1.001 Hrs@ RateureMounting TypeParceurePokage / CaseScon Chang-Ling	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLiad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFirough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601C5187M87
IdentifyAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance180µFTolerance±20%Voltage - Rated600 mOhm @ 100HzESR (Equivalent Series Resistance)600 mOhm @ 100HzDerating Temper.0000 Hrs @ 85°COperating Temperature440°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzImpedance550 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Hounting TypeFolay HolePackage / CaseRadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance180µFTolerance±20%Voltage - Rated600 mOhm @ 100HzESR (Equivalent Series Resistance)600 mOhm @ 100HzDerating Temperature10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzInpedance850 mOhmsSize / Dimension1.181" Dia (30.00mn)Size / Dimension1.01" (27.20mn)Height - Seated (Max)-Mounting TypeForogh HolePoackage / CaseRatial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance180µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature~40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency.133A @ 100HzImpedance850 mOhmsSize / Dimension.334" (10.00mm)Size / Dimension.181" Dia (30.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzImpedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43601
Voltage - Rated450VESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzImpedance850 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Hounting TypeFnough Lande SeatedPackage / CaseRatial, Can - Snap-In	Capacitance	180µF
C600 mOhm @ 100HzESR (Equivalent Series Resistance)600 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequencys50 mOhmsInneedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max).071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Voltage - Rated	450V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	600 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.33A @ 100HzRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a randomRipple Current - High Frequency-Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Applications	General Purpose
Impedance850 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.33A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	850 mOhms
Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.071" (27.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
	Package / Case	Radial, Can - Snap-In
Report en		Report errors?

B43601C5187M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601C5187M87 Payment Methods



If you have any question about B43601C5187M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com