

# B43601C9337M80

#### B43601C9337M80 Information

Heisener.com	 B43601C9337M80 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 330UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43601C9337M80 Specifications

Manufacturer Part Number B43601C9337M80   Manufacturer EPCOS (TDK)   Category Capacitors   Category Capacitors   Package Radial, Can - Snap-In   Series B43601   Capacitance 330µF   Tolerance ±20%   Voltage - Rated 400V   ESR (Equivalent Series Resistance) 300mOhm @100Hz   Lifetime @ Temp. 10000 Hrs @ 85°C   Operating Temperature +40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency 1.63A @ 100Hz   Impedance 450 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Size / Dimension 1.378" Dia (35.00mm)   Size / Dimension -   Height - Seated (Max) -   Mounting Type -   Mounting Type Through Hole		
CategoryCapacitorsAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzDerating Temper10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-163A @ 100HzRipple Current - High Frequency-330 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Manufacturer Part Number	B43601C9337M80
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)30 mOhm @ 100HzDerating Temper300000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationFolaraceApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance450 mOhmsLad Spacing0.394° (10.00mm)Size / Dimension1.378° Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size-Houning TypeFolore ManagementPackage / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance330µFTolerance-20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.0000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationFolarApplicationsGeneral PurposeRipple Current - Low Frequency-6Impedance-30°M (10.00mm)Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension-1071" (72.20mm)Height - Seated (Max)-Mounting Type-Package / CaseMail, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.63A @ 100HzIngedance450 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.071" (27.20mm)Height - Seated (Max)-Mounting TypeThrough HolePoacage / CaseStail, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzESR (Equivalent Series Resistance)10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzImpedance450 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±0%Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzImpedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Series	B43601
Voltage - Rated400VESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzInpedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.071" (27.20mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Capacitance	330µF
C330 mOhm @ 100HzESR (Equivalent Series Resistance)330 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Inneedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	330 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.63A @ 100HzRipple Current - High Frequency-Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance450 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.63A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	450 mOhms
Height - Seated (Max)1.071" (27.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.071" (27.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report erro	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43601C9337M80 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43601C9337M80 Payment Methods





If you have any question about B43601C9337M80, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com