

B43601C9397M87

B43601C9397M87 Information

Heisener.com	Part Number Manufacturer Category Description Package	B43601C9397M87 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 390UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601C9397M87 Specifications

Manufacturer Part NumberB43601C9397M87ManufacturerEPCOS (TDK)CategoryCapacitorsCategoryAluninum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)80000 Hrs @ 85°COperating Temperature440°C - 85°CPolaraGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzLied Spacing380 mOhmsLied Spacing3.378° Dia (35.00mm)Lied Spacing1.378° Dia (35.00mm)Strace Mount Land Size-Mounting Type-Nouting TypeThrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzDerating Temper10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency.196A @ 100HzRipple Current - High Frequency.380 mOhmsLead Spacing.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max).268" (32.20mm)Surface Mount Land Size-Mounting TypeHrough HolePackage / CaseKadia, Can - Snap-In	Manufacturer Part Number	B43601C9397M87
IdentifyAluminum Electrolytic CapacitonsPackageRadial, Can - Snap-InSeriesB43601Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)800 mOhm @ 100HzDerating Temper00000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency380 mOhmsLead Spacing3.38" nOhmsLead Spacing1.378" Dia (35.00mm)Size / Dimension1.268" (32.20mm)Hight - Seated (Max)-Surface Mount Land Size-Hounting TypeHong HolePackage / CaseKaila, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance390µFTolerance420%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzDerating @ Tempe.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency300 mOhmsImpedance309 mOhmsLad Spacing0394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Size / Dimension1.268" (32.20mm)Hight - Seated (Max)-Mounting TypeFinought High FrequencyPounting TypeAida, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance390µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency1.96A @ 100HzInpedance380 mOhmsSize / Dimension1.378" Dia (35.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)-Mounting TypeThrough HolePokage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance990µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency.Ingedance380 mOhmsSize / Dimension.380 mOhmsSize / Dimension.378° Dia (35.00mm)Height - Seated (Max).Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseKadia, Can - Snap-In	Package	Radial, Can - Snap-In
Totrance±0%Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzImpedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFurough Lande SeatedPackage / CaseRadial, Can - Snap-In	Series	B43601
Voltage - Rated400VESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzImpedance380 mOhmsIcad Spacing0.394" (10.00mm)Size / Dimension1.268" (32.20mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFrequencyPackage / CaseRadial, Can - Snap-In	Capacitance	390µF
C280 mOhm @ 100HzESR (Equivalent Series Resistance)280 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Inneedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Tolerance	$\pm 20\%$
Lifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Voltage - Rated	400V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	280 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency1.96A @ 100HzRipple Current - High Frequency-Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance380 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	1.96A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	380 mOhms
Height - Seated (Max)1.268" (32.20mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.268" (32.20mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Dependence of the second se	Package / Case	Radial, Can - Snap-In
Report erro		Report errors?

B43601C9397M87 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601C9397M87 Payment Methods





If you have any question about B43601C9397M87, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com