



B43601E2827M80 Information

Heisener.com

Part NumberB43601E2827M80ManufacturerEPCOS (TDK)CategoryCapacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 250V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43601E2827M80 Specifications

Manufacturer Part NumberB43601E2827M80ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance820µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral Purpose
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43601 Capacitance 820µF Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature Polar
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
PackageRadial, Can - Snap-InSeriesB43601Capacitance $820μF$ Tolerance $±20%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $110 mOhm @ 100Hz$ Lifetime @ Temp. $10000 Hrs @ 85°C$ Operating Temperature $-40°C \sim 85°C$ PolarizationPolar
$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Capacitance $820\mu F$ Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $110 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $10000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolar
Tolerance $\pm 20\%$ Voltage - Rated $250V$ ESR (Equivalent Series Resistance) $110 \text{ mOhm } @ 100\text{Hz}$ Lifetime @ Temp. $10000 \text{ Hrs } @ 85^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ Polarization Polar
Voltage - Rated250VESR (Equivalent Series Resistance)110 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolar
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature Polarization 110 mOhm @ 100Hz 10000 Hrs @ 85°C -40°C ~ 85°C Polarization
Lifetime @ Temp. $10000 \text{Hrs} @ 85^{\circ} \text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$ PolarizationPolar
Operating Temperature -40°C ~ 85°C Polarization Polar
Polarization Polar
Applications General Purpose
Ripple Current - Low Frequency 2.8A @ 100Hz
Ripple Current - High Frequency -
Impedance 150 mOhms
Lead Spacing 0.394" (10.00mm)
Size / Dimension 0.984" Dia (25.00mm)
Height - Seated (Max) 1.858" (47.20mm)
Surface Mount Land Size -
Mounting Type Through Hole
Package / Case Radial, Can - Snap-In
Report errors

B43601E2827M80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601E2827M80 Payment Methods



















B43601E2827M80 Shipping Methods













If you have any question about B43601E2827M80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com