

B43601F2567M

B43601F2567M Information

Heisener.com	Part Number Manufacturer Category Description Package	B43601F2567M EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 560UF 20% 250V SNAP Radial, Can - Snap-In	
	I ackage	For the pricing/inventory/lead time, please contact us	
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43601F2567M Specifications

Manufacturer Part Number B43601F2567M Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series B43601 Copacitance Sefour Tolerance ±20% Voltage - Rated 250V ESR (Equivalent Series Resistance) 160 mOhm @ 100Hz Lifetime @ Temp. 10000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 21 NA @ 100Hz Impedance 22 mOhms Lead Spacing 0.394" (10.0mm) Size / Dimension 0.984" Dia (25.0mm) Height - Seated (Max) 3.094" (10.0mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Kadia, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzLipple Current - High Frequency-Impedance0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43601F2567M
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - High Frequency2.18A @ 100HzLinedance2.090 m/smLinedance0.394° (10.00mm)Siz / Dimension0.984° Dia (25.00mm)Siz / Dimension1.457° (37.00mm)Hight - Seated (Max)-Munting Type-Package / CaseMaid, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43601Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLied Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFackage / CasePackage / CaseRadial, Can - Snap-In	Category	Capacitors
SeriesB43601Capacitance560µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzLifed Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFurough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance560μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Impedance20 mOhmsLad Spacing0.984" 10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±2%Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarzationPolarApplicationsGeneral PurposeRipple Current - High Frequency2.18A @ 100HzImpedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In	Series	B43601
Voltage - Rated250VESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In	Capacitance	560µF
ESR (Equivalent Series Resistance)160 mOhm @ 100HzLifetime @ Temp.10000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzLingedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeFinough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.10000 Hrs @ 85°CDeperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	160 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	10000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency2.18A @ 100HzRipple Current - High Frequency-Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance220 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	2.18A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	220 mOhms
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In
		Report errors?

B43601F2567M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43601F2567M Payment Methods



If you have any question about B43601F2567M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com