

## B43624E2108M000

#### B43624E2108M000 Information

Heisener.com	 B43624E2108M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 1000UF 20% 250V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### B43624E2108M000 Specifications

Manufacturer EPCOS (TDK)   Category Capacitors   Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors   Package Radial, Can - Snap-In   Series B43624   Capacitance 1000µF   Tolerance ±20%   Voltage - Rated 250V   ESR (Equivalent Series Resistance) 90 mOhm @ 100Hz   Lifetime @ Temp. 8000 Hrs @ 85°C   Operating Temperature -40°C ~ 85°C   Polarization General Purpose   Applications General Purpose   Ripple Current - Low Frequency -   Impedance 140 mOhms   Lead Spacing 0.394" (10.00mm)   Size / Dimension 1.181" Dia (30.00mm)   Height - Seated (Max) 1.850" (47.00mm)   Surface Mount Land Size -   Mounting Type Through Hole   Package / Case Kadial, Can - Snap-In	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43624Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Manufacturer Part Number	B43624E2108M000
Aluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InStriesB43624Capacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)00 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeApplications5.53 A @ 100HzRipple Current - High Frequency-Impedance1.40 mOhmsLided Spacing0.394" (10.00mm)Siz / Dimension1.81" Dia (30.00mm)Siz / Dimension1.850" (47.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43624Capacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency-Riple Current - High Frequency-Impedance140 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Package / CaseKadial, Can - Snap-In	Category	Capacitors
SeriesB43624Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzLied Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKadial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzImpedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Pockage / CaseRadial, Can - Snap-In	Series	B43624
Voltage - Rated250VESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzImpedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In	Capacitance	1000µF
ESR (Equivalent Series Resistance)90 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzBipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp.8000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeFackage / CaseRadial, Can - Snap-InRadial, Can - Snap-In	Voltage - Rated	250V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	ESR (Equivalent Series Resistance)	90 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lifetime @ Temp.	8000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency3.53A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency3.53A @ 100HzRipple Current - High Frequency-Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Polarization	Polar
In a constraint of the product of t	Applications	General Purpose
Impedance140 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3.53A @ 100Hz
IILead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Impedance	140 mOhms
Height - Seated (Max)1.850" (47.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Size / Dimension	1.181" Dia (30.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Height - Seated (Max)	1.850" (47.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

#### B43624E2108M000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### B43624E2108M000 Payment Methods



If you have any question about B43624E2108M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com