

B43634B9157M000

B43634B9157M000 Information

Heisener.com	 B43634B9157M000 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors CAP ALUM 150UF 20% 400V SNAP Radial, Can - Snap-In For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43634B9157M000 Specifications

Manufacturer Part NumberB43634B9157M000ManufacturerEPCOS (TDK)CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43634Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzDerating Temperature>25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.13 A@ 100HzRipple Current - High Frequency.Liad Spacing0.984° (10.0mm)Size / Dimension0.984° Dia (25.0mm)Kirge Kuman Sama1.062° (27.0mm)Surface Mount Land Size.Nurting TypeInrough HoleSurface Mount Land SizeNurue MoleSurface Mount Land SizeNurue Mole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43634Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency-11 OhmsInpedance1.1 OhmsLad Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer Part Number	B43634B9157M000
IdentifyAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesB43634Capacitance150µFTolerance±20%Voltage - Rated000VESR (Equivalent Series Resistance)720 mOhm @ 100HzDerating Temperature8000 Hrs @ 85°COpariang Temperature25°C ~ 85°CPolarizationGeneral PurposeApplications6 General PurposeRippe Current - High Frequency.113A @ 100HzImpedance1.10hmsLead Spacing0.394" (1.00mm)Size / Dimension.984" Dia (25.00mm)Hight - Seated (Max).162" (27.00mm)Mounting TypeThrough Hole	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-InSeriesB43634Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzImpedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesB43634Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzImpedance1.10hnsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance150µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-113A @ 100HzInpedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)-Mounting TypeThrough Hole	Package	Radial, Can - Snap-In
Tolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzImpedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Series	B43634
Voltage - Rated400VESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.984" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Capacitance	150µF
Construct720 mOhm @ 100HzESR (Equivalent Series Resistance)720 mOhm @ 100HzLifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.934" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land SizeThrough Hole	Tolerance	±20%
Lifetime @ Temp.8000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Voltage - Rated	400V
Operating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	ESR (Equivalent Series Resistance)	720 mOhm @ 100Hz
PolarizationPolarPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lifetime @ Temp.	8000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency1.13A @ 100HzRipple Current - High Frequency-Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Polarization	Polar
In a constraint of the second secon	Applications	General Purpose
Impedance1.1 OhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - Low Frequency	1.13A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	-
Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	1.1 Ohms
Height - Seated (Max)1.062" (27.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough Hole	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole	Height - Seated (Max)	1.062" (27.00mm)
	Surface Mount Land Size	-
	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report er		Report errors?

B43634B9157M000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43634B9157M000 Payment Methods





If you have any question about B43634B9157M000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com