



B43640A2158M000 Information



For Reference Only

Part Number B43640A2158M000 Manufacturer EPCOS (TDK) Category

Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1500UF 20% 200V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43640A2158M000 Specifications

Manufacturer Part Number B43640A2158M000 Manufacturer EPCOS (TDK) Category Capacitors Package Radial, Can - Snap-In Series B43640 Capacitance 1500μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Lead Spacing 0.394" (10.00mm) Size / Dimension 0.994" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	*	
Category Capacitors Package Radial, Can - Snap-In Series B43640 Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	B43640A2158M000
Package Radial, Can - Snap-In Series B43640 Capacitance 1500μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	EPCOS (TDK)
Package Radial, Can - Snap-In Series B43640 Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series B43640 Capacitance 1500μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 1500µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) 65 mOhm @ 100Hz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	B43640
Voltage - Rated200VESR (Equivalent Series Resistance)65 mOhm @ 100HzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3A @ 100HzRipple Current - High Frequency-Impedance95 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Capacitance	1500μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency -Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 105°C -40°C ~ 105°C	Voltage - Rated	200V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	65 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency 3A @ 100Hz Ripple Current - High Frequency - Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance 95 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Applications	General Purpose
Impedance95 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - Low Frequency	3A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension0.984" Dia (25.00mm)Height - Seated (Max)2.244" (57.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In	Ripple Current - High Frequency	-
Size / Dimension 0.984" Dia (25.00mm) Height - Seated (Max) 2.244" (57.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	95 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	0.984" Dia (25.00mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	2.244" (57.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
-	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
		Report errors?

B43640A2158M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43640A2158M000 Payment Methods


































If you have any question about B43640A2158M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com