

B43644B9477M002

B43644B9477M002 Information

Container com	Part Number Manufacturer Category Description Package	B43644B9477M002 EPCOS (TDK) Capacitors Aluminum Electrolytic Capacitors ALUMINIUM ELECTROLYTIC SNAP-IN 4 Radial, Can - Snap-In - 3 Lead For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43644B9477M002 Specifications

Manufacturer Part Number B43644B9477M002 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In - 3 Lead Series B43644 Capacitance 470µF Tolerance 420% Voltage - Rated 400V ESR (Equivalent Series Resistance) 210 mOhm @ 100Hz Lifetime @ Temp. 5000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization General Purpose Applications General Purpose Ripple Current - Low Frequency 1.92A @ 100Hz Impedance 3.01 mOhms Lead Spacing 0.394" (10.00mm) Size / Dimension 1.378" bia (35.00mm) Size / Dimension 3.78" bia (35.00mm) Size / Dimension - Mounting Type Through Hole Mounting Type Fhrough Hole	-	
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43644Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLized Spacing0.394" (10.00mm)Size / Dinension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeFhrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer Part Number	B43644B9477M002
Auminum Electrolytic CapacitorsPackageRadial, Can - Snap-In - 3 LeadSeriesB43644Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Size / Dimension1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Snap-In - 3 LeadSeriesB43644Capacitance470μFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzImpedance309 mOhmsLad Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeForoghenePackage / CaseRadial, Can - Snap-In - 3 Lead	Category	Capacitors
SeriesB43644Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzESR (Equivalent Series Resistance)5000 Hrs @ 105°COperating Temperature-40°C ~ 105°COperating TemperaturePolarApplicationsGeneral PurposeRipple Current - High Frequency1.92A @ 100HzInpedance310 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.460° (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseKailal, Can - Snap-In - 3 Lead		Aluminum Electrolytic Capacitors
Capacitance470µFTolerance±20%Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzESR (Equivalent Series Resistance)5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency1.92A @ 100HzInpedance310 mOhmsSize / Dimension1.378° Dia (35.00mm)Size / Dimension1.460° (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseKail, Can - Snap-In - 3 Lead	Package	Radial, Can - Snap-In - 3 Lead
Tolerance±0%Yoltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency.Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max).Surface Mount Land Size-Mounting TypeRatial, Can - Snap-In - 3 Lead	Series	B43644
Voltage - Rated400VESR (Equivalent Series Resistance)210 mOhm @ 100HzLifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzImpedance310 mOhmsIszer / Dimension.378" Dia (35.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max).460" (37.00mm)Surface Mount Land Size.Mounting TypeThrough HolePackage / CaseRatial, Can - Snap-In - 3 Lead	Capacitance	470µF
For a constraint of a constrai	Tolerance	$\pm 20\%$
Lifetime @ Temp.5000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.460" (37.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can - Snap-In - 3 Lead	Voltage - Rated	400V
Operating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.450" (37.00mm)Height - Seated (Max)-Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	ESR (Equivalent Series Resistance)	210 mOhm @ 100Hz
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lifetime @ Temp.	5000 Hrs @ 105°C
ApplicationsGeneral PurposeRipple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency1.92A @ 100HzRipple Current - High Frequency-Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Polarization	Polar
In a constraint of a constrain	Applications	General Purpose
Impedance310 mOhmsLead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - Low Frequency	1.92A @ 100Hz
Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Ripple Current - High Frequency	-
Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Impedance	310 mOhms
Height - Seated (Max)1.460" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Size / Dimension	1.378" Dia (35.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In - 3 Lead	Height - Seated (Max)	1.460" (37.00mm)
Package / Case Radial, Can - Snap-In - 3 Lead	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors	Package / Case	Radial, Can - Snap-In - 3 Lead
		Report errors?

B43644B9477M002 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43644B9477M002 Payment Methods





If you have any question about B43644B9477M002, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com