

B43699B5226Q Information

Heisener.com

Part Number B43699B5226Q
Manufacturer EPCOS (TDK)
Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 450V AXIAL

Package Axial, Can

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43699B5226Q Specifications

Manufacturer Part NumberB43699B5226QManufacturerEPCOS (TDK)CategoryCapacitorsPackageAxial, CanSeriesB43699Capacitance22µFTolerance-10%, +30%Voltage - Rated450VESR (Equivalent Series Resistance)4.6 Ohm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency870mA @ 10kHzImpedance2 OhmsLead Spacing-Size / Dimension0.524" Dia x 1.535" L (13.30mm x 39.00mm)Height - Seated (Max)-Surface Mount Land Size-	C 1	
Category Capacitors Aluminum Electrolytic Capacitors Package Axial, Can Series B43699 Capacitance 22µF Tolerance -10%, +30% Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency B70mA @ 10kHz Impedance 2 Ohms Lead Spacing 5ize / Dimension Height - Seated (Max) Capacitors Axial, Can Axial,	Manufacturer Part Number	B43699B5226Q
PackageAxial, CanSeriesB43699Capacitance22μFTolerance-10%, +30%Voltage - Rated450VESR (Equivalent Series Resistance)4.6 Ohm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency870mA @ 10kHzImpedance2 OhmsLead Spacing-Size / Dimension0.524" Dia x 1.535" L (13.30mm x 39.00mm)Height - Seated (Max)-	Manufacturer	EPCOS (TDK)
Package Axial, Can Series B43699 Capacitance 22μF Tolerance -10%, +30% Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Category	Capacitors
Series B43699 Capacitance 22μF Tolerance -10%, +30% Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance -10%, +30% Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Package	Axial, Can
Tolerance -10%, +30% Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Series	B43699
Voltage - Rated 450V ESR (Equivalent Series Resistance) 4.6 Ohm @ 100Hz Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing Size / Dimension Height - Seated (Max) 4.6 Ohm @ 100Hz 4.6 Ohm @ 100Hz 6000 Hrs @ 105°C -40°C ~ 105°C Polar 40°C ~ 105°C -40°C ~ 105°C	Tolerance	-10%, +30%
Lifetime @ Temp. 6000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Voltage - Rated	450V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	ESR (Equivalent Series Resistance)	4.6 Ohm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Lifetime @ Temp.	6000 Hrs @ 105°C
Applications General Purpose Ripple Current - Low Frequency	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency - 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Polarization	Polar
Ripple Current - High Frequency 870mA @ 10kHz Impedance 2 Ohms Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Applications	General Purpose
Impedance2 OhmsLead Spacing-Size / Dimension0.524" Dia x 1.535" L (13.30mm x 39.00mm)Height - Seated (Max)-	Ripple Current - Low Frequency	-
Lead Spacing - Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Ripple Current - High Frequency	870mA @ 10kHz
Size / Dimension 0.524" Dia x 1.535" L (13.30mm x 39.00mm) Height - Seated (Max) -	Impedance	2 Ohms
Height - Seated (Max)	Lead Spacing	-
	Size / Dimension	0.524" Dia x 1.535" L (13.30mm x 39.00mm)
Surface Mount Land Size -	Height - Seated (Max)	-
	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Axial, Can	Package / Case	Axial, Can
Report errors?		Report errors?

B43699B5226Q Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43699B5226Q Payment Methods





















B43699B5226Q Shipping Methods













If you have any question about B43699B5226Q, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com