



B43713A5109M000 Information

Heisener.com

Part Number B43713A5109M000 Manufacturer EPCOS (TDK)

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 10000UF 20% 450V SCREW

Package Radial, Can - Screw Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









B43713A5109M000 Specifications

Manufacturer Part Number B43713A5109M000 Manufacturer EPCOS (TDK) Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries B43713 Capacitance 10000µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ı	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Screw Terminals Scries B43713 Capacitance 10000µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 4.740" (222.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer Part Number	B43713A5109M000
Package Radial, Can - Screw Terminals Series B43713 Capacitance 10000µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Manufacturer	EPCOS (TDK)
PackageRadial, Can - Screw TerminalsSeriesB43713Capacitance10000μFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)12 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28.3A @ 100HzRipple Current - High Frequency-Impedance20 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Category	Capacitors
Series B43713 Capacitance 10000µF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals		Aluminum Electrolytic Capacitors
Capacitance 10000μF Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Package	Radial, Can - Screw Terminals
Tolerance ±20% Voltage - Rated 450V ESR (Equivalent Series Resistance) 12 mOhm @ 100Hz Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Series	B43713
Voltage - Rated450VESR (Equivalent Series Resistance)12 mOhm @ 100HzLifetime @ Temp.15000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency28.3A @ 100HzRipple Current - High Frequency-Impedance20 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Capacitance	10000μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Tolerance	±20%
Lifetime @ Temp. 15000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Voltage - Rated	450V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	ESR (Equivalent Series Resistance)	12 mOhm @ 100Hz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lifetime @ Temp.	15000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 28.3A @ 100Hz Ripple Current - High Frequency - Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Polarization	Polar
Ripple Current - High Frequency Impedance 20 mOhms Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Applications	General Purpose
Impedance20 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.543" Dia (90.00mm)Height - Seated (Max)8.740" (222.00mm)Surface Mount Land Size-Mounting TypeChassis MountPackage / CaseRadial, Can - Screw Terminals	Ripple Current - Low Frequency	28.3A @ 100Hz
Lead Spacing 1.248" (31.70mm) Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Ripple Current - High Frequency	-
Size / Dimension 3.543" Dia (90.00mm) Height - Seated (Max) 8.740" (222.00mm) Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Impedance	20 mOhms
Height - Seated (Max) Surface Mount Land Size Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Lead Spacing	1.248" (31.70mm)
Surface Mount Land Size - Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Size / Dimension	3.543" Dia (90.00mm)
Mounting Type Chassis Mount Package / Case Radial, Can - Screw Terminals	Height - Seated (Max)	8.740" (222.00mm)
Package / Case Radial, Can - Screw Terminals	Surface Mount Land Size	-
-	Mounting Type	Chassis Mount
Report errors?	Package / Case	Radial, Can - Screw Terminals
		Report errors?

B43713A5109M000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

B43713A5109M000 Payment Methods



















B43713A5109M000 Shipping Methods













If you have any question about B43713A5109M000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com