

B43740A5338M3

Request a Quote

B43740A5338M3 Information

Heisener.com	Part Number	B43740A5338M3
	Manufacturer	EPCOS (TDK)
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 3300UF 20% 450V SCREW
	Package	Radial, Can - Screw Terminals
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



B43740A5338M3 Specifications

Manufacturer Part NumberB43740A5338M3ManufacturerEPCOS (TDK)CategoryCapacitorsPackageAluninun Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43740Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.14A @ 100HzLied Spacing32 mOhmsLead Spacing3.028" Dia (76.90mm)Size / Dimension5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis MountPackage / CaseKadia, Can - Screw Terminals		-
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43740Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzESR (Equivalent Series Resistance)6000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.14A @ 100HzRipple Current - High Frequency32 mOhmsLead Spacing3.028" Dia (76.90mm)Size / Dimension5.185" (131.70mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis Mount	3740A5338M3	Manufacturer Part Number
Aluminum Electrolytic CapacitorsPackageRadial, Can - Screw TerminalsSeriesB43740Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationReneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzImpedance32 mOhmsLead Spacing3.028" Dia (76.90mm)Size / Dimension5.185" (131.70mm)Mounting TypeChassis Mount	COS (TDK)	Manufacturer
PackageRadial, Can - Screw TerminalsSeriesB43740Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzDerating Temper6000 Hrs @ 105°COperating Temperature-PolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency1.14A @ 100HzInpedance32 mOhmsLead Spacing3.2 mOhmsSize / Dimension3.028" bia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis Mount	pacitors	Category
SeriesB43740Series3300µFCapacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension5.185" (131.70mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	uminum Electrolytic Capacitors	
Capacitance3300µFTolerance±20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzImpedance32 mOhmsLead Spacing3.28 mOhmsSize / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis Mount	dial, Can - Screw Terminals	Package
Tolerance£20%Voltage - Rated450VESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - High Frequency-Imedance32 mOhmsLead Spacing3.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)-Mounting TypeChasis Mount	3740	Series
Voltage - Rated450VVoltage - Rated27 mOhm @ 100HzESR (Equivalent Series Resistance)27 mOhm @ 100FzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension5.185" (131.70mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis Mount	00µF	Capacitance
ESR (Equivalent Series Resistance)27 mOhm @ 100HzLifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing3.028" Dia (76.90mm)Size / Dimension5.185" (131.70mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChasis Mount	0%	Tolerance
Lifetime @ Temp.6000 Hrs @ 105°COperating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	0V	Voltage - Rated
Operating Temperature-PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension5.185" (131.70mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	mOhm @ 100Hz	ESR (Equivalent Series Resistance)
PolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	00 Hrs @ 105°C	Lifetime @ Temp.
ApplicationsGeneral PurposeRipple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount		Operating Temperature
Ripple Current - Low Frequency11.4A @ 100HzRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	lar	Polarization
InInRipple Current - High Frequency-Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	neral Purpose	Applications
Impedance32 mOhmsLead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	.4A @ 100Hz	Ripple Current - Low Frequency
Lead Spacing1.248" (31.70mm)Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount		Ripple Current - High Frequency
Size / Dimension3.028" Dia (76.90mm)Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	mOhms	Impedance
Height - Seated (Max)5.185" (131.70mm)Surface Mount Land Size-Mounting TypeChassis Mount	248" (31.70mm)	Lead Spacing
Surface Mount Land Size-Mounting TypeChassis Mount)28" Dia (76.90mm)	Size / Dimension
Mounting Type Chassis Mount	85" (131.70mm)	Height - Seated (Max)
		Surface Mount Land Size
Package / Case Radial, Can - Screw Terminals	assis Mount	Mounting Type
	dial, Can - Screw Terminals	Package / Case
Repor	Report errors?	

B43740A5338M3 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

B43740A5338M3 Payment Methods





If you have any question about B43740A5338M3, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com